

BALDOR® • RELIANCE™

Customer information packet 407B

28C 4P BUFFER

Specifications

Frequency	60.00 Hz
Nameplate Output	1
Number of Poles	4
Phase	1
Product Style	BUFFER
Shaft Diameter	0.875 IN
Speed	1800 rpm
Voltage	115 V 230 V

Part detail

Revision	AV
Type	AC
Mech. spec.	G10-168
Base	
Status	PRD/A
Elec. spec.	G0WG0002
Layout	G0LY0168
Eff. date	12-15-2021
CD Diagram	CD0279
Poles	04
Leads	4#18 12" LG Y
Proprietary	False
Created date	01-01-0001

Nameplate

NP3352L			
CAT.NO.	407B		
HP	1	VOLTS	115/230
PHASE	1	AMPS	5.4/2.7
HZ	60	RPM	1800
SER.NO			
SPEC.	G10-168-2		
BLANK			

Accessories

Part number	Description	Multiplier
GA16	PEDESTAL INDUSTRIAL, CAST IRON 6" - 10"	A8
GA14	PEDESTAL FABRICATED STEEL W/SHELVES	A8
GA20	PEDESTAL INDUSTRIAL, CAST IRON 8"-14"	A8
GA20E	PEDESTAL LIGHT INDUSTRIAL,STEEL	A8
A103	10" COTTON BUFFING WHEEL (G0AP3004)	A8
BQ1-015-CC	1PH Brake, NEMA 1,110-125 VAC, 50/60Hz	
BQ1-015-CP	1PH Brake, Panel 110-125 VAC, 50/60 Hz	



