

ABB BALDOR RELIANCE III

Customer information packet

CL5003A

.5HP, 3450RPM, 1PH, 60HZ, 56C, X3416L, XPFC, F1

Class - CLI GP D; CLII GP F,G

Division - Division I

Specifications

Enclosure	XPFC
Frame	56C
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	CLI GP D; CLII GP F,G
Haz Area Division	Division I
Motor Letter Type	Cap Start, Induction Run
Output @ Frequency	.500 HP @ 60 HZ
Phase	1
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	115.0 V @ 60 HZ 230.0 V @ 60 HZ
Agency Approvals	UL CSA UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	3.700 A @ 230.0 V 7.400 A @ 115.0 V
Design Code	N
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	57.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Haz Area Temp Code	T3C

Part Detail

Revision	AM
Type	AC
Mech. spec.	34-5328
Base	
Status	PRD/A
Elec. spec.	34WG5719
Layout	34LY5328
Eff. date	03-02-2026
CD Diagram	CD0565
Poles	02
Leads	6#18,1#16 #4TH
Proprietary	False
Created date	01-01-0001

Heater Indicator	No Heater
High Voltage Full Load Amps	3.7 a
Insulation Class	B
Inverter Code	Not Inverter
KVA Code	K
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	6 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3416L
Mounting Arrangement	F1
Number of Poles	2
Overall Length	13.22 IN
Power Factor	71
Product Family	Hazardous Location Motor
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.00
Shaft Diameter	0.625 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	3450 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor



Winding Thermal 1	Automatic Thermal Overload
Winding Thermal 1 Location	SB

Nameplate

NP0016XPSL									
NO.		CC							
SER. #									
SPEC	34-5328-5719								
CAT.NO.	CL5003A								
H.P.	.5	T. CODE	T3C						
VOLTS	115/230								
AMPS	7.4/3.7								
R.P.M.	3450								
HZ	60	PH	1	CLASS	B				
SER.F.	1.00	DES	N	CODE	K				
RATING	40C AMB-CONT								
FRAME	56C	NEMA NOM. EFF	57						
	PF	71							
BLANK									

AC Induction Motor Performance Data

Record # 6817

Typical performance - not guaranteed values

Winding: 34WG5719-R001				Type: 3416L		Enclosure: XPFC	
Nameplate Data				230 V, 60 Hz: High Voltage Connection			
Rated Output (HP)		.5		Full Load Torque		0.75 LB-FT	
Volts		115/230		Start Configuration		direct on line	
Full Load Amps		7.4/3.7		Breakdown Torque		2 LB-FT	
R.P.M.		3450		Pull-up Torque		1.6 LB-FT	
Hz	60	Phase	1	Locked-rotor Torque		3 LB-FT	
NEMA Design Code		N	KVA Code	K	Starting Current		18.5 A
Service Factor (S.F.)		1		No-load Current		2.95 A	
NEMA Nom. Eff.		57	Power Factor	71	Line-line Res. @ 25°C		4.72 Ω A Ph 3.76 Ω B Ph
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		78°C	

Load Characteristics 230 V, 60 Hz, 0.5 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	39	49	61	69	74	78
Efficiency	38.3	49.7	57.4	60.7	60.9	59.8
Speed	3530	3490	3450	3420	3380	3340
Line amperes	3	3.2	3.5	3.9	4.4	4.95


ABB Motors and Mechanical Inc.


WINDING # 34WG5719

Typical performance - not guaranteed values.


0.5 HP 1 PH 60 HZ 3450 RPM 230 V 3416L

TORQUES (LB-FT) : PO=2 PU=1.6 LR=3 LRA=18.5






CD0565



	LINE A	LINE B	JOIN	JOIN
HIGH STD	1	4	2,3,8	J,5
HIGH OPP	1	4	2,3,5	J,8
LOW STD	1,3,8	4	—	2,J,5
LOW OPP	1,3,5	4	—	2,J,8

- NOTES:
1. STANDARD ROTATION IS CCW FACING END OPPOSITE SHAFT EXTENSION.
 2. MULTIPLE CAPACITORS ARE CONNECTED IN PARALLEL UNLESS OTHERWISE SPECIFIED.
 3. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

CONNECTIONS FOR TWO-TERMINAL THERMAL



CD0565

REV. DESC: REVISE TO SHOW OPTIONAL COLORS			
REV. LTR: C	BY: JLP	REVISED: 04/08/99 3:25	TDR: 0178636
FILE: AAA00014311		MDL: —	
MTL: —			

BALDOR ELECTRIC Co.

TYPE L, DV, REV, THERMAL, 7 LD, 34XP