

BALDOR • RELIANCE

Customer information packet

CXL050342A-50

.33HP, 1425RPM, 1PH, 50HZ, 56C, 3421L, XPFC, F1

Class - CLI GP D; CLII GP F,G

Division - Division I

Specifications

Enclosure	XPFC
Frame	56C
Frame Material	Steel
Frequency	50.00 Hz
Haz Area Class and Group	CL I GP D; CL II GP F,G
Haz Area Division	Division I
Motor Letter Type	Cap Start, Induction Run
Output @ Frequency	.330 HP @ 50 HZ
Phase	1
Synchronous Speed @ Frequency	1500 RPM @ 50 HZ
Voltage @ Frequency	110.0 V @ 50 HZ 220.0 V @ 50 HZ
Agency Approvals	CSA UL
Ambient Temperature	40 °C
Auxillary Box	No Auxillary Box
Auxillary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	2.600 A @ 220.0 V 5.200 A @ 110.0 V
Design Code	N
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	59.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Haz Area Temp Code	T3C
Heater Indicator	No Heater
High Voltage Full Load Amps	2.6 a
Insulation Class	B

Part detail

Revision	D
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	34WGW777
Layout	34LY5328
Eff. date	05-01-2024
CD Diagram	CD0565
Poles	04
Leads	7#18
Proprietary	False
Created date	03-30-2021

Inverter Code	Not Inverter
IP Rating	NONE
KVA Code	L
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3421L
Mounting Arrangement	F1
Number of Poles	4
Overall Length	14.22 IN
Power Factor	68
Product Family	Hazardous Location Motor
Pulley Face Code	C-Face
Rodent Screen	None
Service Factor	1.00
Shaft Diameter	0.625 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Speed	1425 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	Automatic Thermal Overload
Winding Thermal 1 Location	SK
Winding Thermal 2	None

Nameplate

NP0016XPSL				
NO.		CC		
SER. #				
SPEC	34-0000-0410			
CAT.NO.	CXL050342A-50			
H.P.	.33	T. CODE	T3C	
VOLTS	110/220			
AMPS	5.2/2.6			
R.P.M.	1425 34WGW777			
HZ	50	PH	1	CLASS B
SER.F.	1.00	DES	N	CODE L
RATING	40C AMB-CONT			
FRAME	56C	NEMA NOM. EFF	59.5	
	PF	68		
BLANK	NEMA MG-1 PART 5, IP54			

AC Induction Motor Performance Data

Record # 7096

Typical performance - not guaranteed values

Winding: 34WGW777-R001		Type: 3421L		Enclosure: XPFC	
Nameplate Data			220 V, 50 Hz: High Voltage Connection		
Rated Output (HP)	.33		Full Load Torque	1.2 LB-FT	
Volts	110/220		Start Configuration	direct on line	
Full Load Amps	5.2/2.6		Breakdown Torque	2.6 LB-FT	
R.P.M.	1425		Pull-up Torque	1.9 LB-FT	
Hz	50 Phase	1	Locked-rotor Torque	3.3 LB-FT	
NEMA Design Code	N KVA Code	L	Starting Current	13 A	
Service Factor (S.F.)	1		No-load Current	2.25 A	
NEMA Nom. Eff.	59.5 Power Factor	68	Line-line Res. @ 25°C	6.72 Ω A Ph 6.74 Ω B Ph	
Rating - Duty	40C AMB-CONT		Temp. Rise @ Rated Load	80°C	

Load Characteristics 220 V, 50 Hz, 0.33 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	35	46	56	65	72	78
Efficiency	35.1	50.6	58.3	62.2	63.6	63.3
Speed	1480	1467	1452	1436	1416	1393
Line amperes	2.3	2.4	2.55	2.75	3.15	3.45


ABB Motors and Mechanical Inc.

WINDING # 34WG777


0.33 HP 1 PH 50 HZ 1425 RPM 220 V 3421L

Typical performance - not guaranteed values.


TORQUES (LB-FT): PO=2.6 PU=1.9 LR=3.3 LRA=13



5/29/2024 ACPERF, record # 7096



CD0565




	LINE A	LINE B	JOIN	JOIN
HIGH STD	1	4	2,3,8	J,5
HIGH OPP	1	4	2,3,5	J,8
LOW STD	1,3,8	4	-	2,J,5
LOW OPP	1,3,5	4	-	2,J,8

NOTES:

1. STANDARD ROTATION IS CCW FACING END OPPOSITE SHAFT EXTENSION.
2. MULTIPLE CAPACITORS ARE CONNECTED IN PARALLEL UNLESS OTHERWISE SPECIFIED.
3. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

CONNECTIONS FOR TWO-TERMINAL THERMAL



REV. DESC: REVISE TO SHOW OPTIONAL COLORS			
REV. LTR: C	BY: JLP	REVISED: 04/08/99 3:25	TDR: 0178636
99000		FILE: AAA00014311	MDL: -
		MTL: -	

BALDOR ELECTRIC Co.

TYPE L, DV, REV, THERMAL, 7 LD, 34XP

CD0565