ABB BALDOR RELIANCE

Customer information packet

DRX141544T

1.5//1HP, 1770//1475RPM, 3PH, 60//50HZ, 145T
Class - CLI GP C,D
Division - Division I

Copyright © All product information within this document is subject to ABB Motors and Mechanical Inc. copyright © protection, unless otherwise noted.
11/16/2026 12:08:04 PM

Specifications

Enclosure	XPFC
Frame	145T
Frame Material	Steel
Frequency	50.00 Hz
	60.00 Hz
Haz Area Class and Group	CLI GP C,D
Haz Area Division	Division I
Motor Letter Type	Three Phase
Output @ Frequency	1.500 HP @ 60 HZ
	1.000 HP @ 50 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	190.0 V @ 50 HZ
	230.0 V @ 60 HZ
	380.0 V @ 50 HZ
	460.0 V @ 60 HZ
Agency Approvals	CSA EEV
	UL
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	4.640 A @ 208.0 V
	4.600 A @ 230.0 V
	4.000 A @ 190.0 V
	2.300 A @ 460.0 V
	2.000 A @ 380.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT

Part Detail

Revision	C
Type	AC
Mech. spec.	35X081
Base	
Status	PRD/A
Elec. spec.	35WGL955
Layout	35LYX081
Eff. date	05-20-2024
CD Diagram	CD0005
Poles	04
Leads	9#18
Proprietary	False
Created date	02-23-2023

Efficiency @ 100% Load	86.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	2.0 a
Insulation Class	F
Inverter Code	Inverter Duty
KVA Code	M
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Max Speed	2700 rpm
Motor Lead Quantity/Wire Size	9 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3526M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	15.09 IN
Power Factor	72
Product Family	Hazardous Location Motor
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS NON-COMPLIANT
Service Factor	1.00
Shaft Diameter	0.875 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Speed	1475 rpm
	1770 rpm
Speed Code	Single Speed
Starting Method	Direct on line

Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1401XPSLEV											
NO.				**CC**							
S/N				**TEMP CODE**	T3C						
SPEC.	35X081L955			**INV.TYPE**	PWM						
CAT.NO.	DRX141544T			**C HP FR**	60	**C HP TO**	90				
HP	1.5//1			**CT HZ FROM**	6			**CT HZ TO**	60		
VOLTS	230/460//190/380			**VT HZ FROM**	6			**VT HZ TO**	60		
AMPS	4.6/2.3//4/2			**MAG CUR**	3/1.5						
RPM	1770//1475			**MX RPM**	2700						
HZ	60//50	**PH**	3	**CL**	F	**NOM.EFF.**	86.5				
SER.F.	1.00	**DES**	B	**SL HZ**	1	**WK2**	0.174				
FRAME	145T	**RATING**	40C AMB-CONT								
	55C AMB @ 1.0 SF										
	1.15 SF SINEWAVE				NEMA MG-1 PT 5,IP55						

AC Induction Motor Performance Data
Record # 73666
Typical performance - not guaranteed values

Winding: 35WGL155-R039	**Type:** 3526M	**Enclosure:** XPFC

Nameplate Data			
Rated Output (HP)			1.5//1
Volts			230/460//190/380
Full Load Amps			4.4/2.2//4/2
R.P.M.			1760//1460
Hz	60//50	**Phase**	3
NEMA Design Code	B	**KVA Code**	M
Service Factor (S.F.)			1
NEMA Nom. Eff.	86.5	**Power Factor**	71
Rating - Duty			40C AMB-CONT

460 V, 60 Hz: High Voltage Connection	
Full Load Torque	4.46 LB-FT
Start Configuration	direct on line
Breakdown Torque	20.6 LB-FT
Pull-up Torque	10.1 LB-FT
Locked-rotor Torque	14.4 LB-FT
Starting Current	19.3 A
No-load Current	1.46 A
Line-line Res. @ 25ºC	8.81 Ω
Temp. Rise @ Rated Load	42°C
Locked-rotor Power Factor	49.6
Rotor inertia	0.154 LB-FT2

Load Characteristics 460 V, 60 Hz, 1.5 HP

% of Rated Load	**25**	**50**	**75**	**100**	**125**	**150**
Power Factor	30	49	63	71	77	82
Efficiency	76.3	84.6	87	87.5	87	86
Speed	1791	1782	1772	1762	1750	1738
Line amperes	1.53	1.68	1.92	2.24	2.62	3


ABB Motors and Mechanical Inc.

WINDING # 35WGL155


1.5 HP 3 PH 60 HZ 1762 RPM 460 V 3526M

Typical performance - not guaranteed values.


TORQUES(LB-FT): PO=20.6 PU=10.1 LR=14.4 LRA=19.3




11/16/2026 ACPERF, record # 73666


35LYX081
510-520 = 14.22
521-528 = 15.09
529-535 = 15.97
536 - 546 = 17.34
2.60
2.25
.19 KEY
1.38 LONG
Ø7.19
X-PROOF NAMEPLATE
FOR HAZARDOUS LOCATIONS
Ø .8750
.8745
DRAINS
(EACH END)
4.60
4.00
2.25
5.00
.50
5.94
6 HOLES
.38 WIDE
6.67
7.21
7.08
3.50
3.44
LEAD HOLE
.75 N.P.T.
2.75
2.75
4.82
3.25
6.50
.0015 MAX
CLEARANCE
(EACH END)
.09
.38
.019 MAX
DIAMETRICAL
CLEARANCE
.006
.004
.37
1.00
(MIN)
DRIVE END DETAIL
CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT THE PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION
REV. DESC: LOAD TO SOLIDWORKS
REV: D
VERSION: 04
REVISED: 01:07:11 08/30/2019
TDR: 000001117187
MODEL NO. 35LYX081
REF: -
BY: USBUFRA
B
BALDOR - RELIANCE®
HORZ 143-5T XPFC 35M CL-I GP-C&D, DRILL RIG W/FACE DRAINS
35LYX081

CD0005





NOTES:

1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

CD0005

REV. DESC: REVISE TO SHOW OPTIONAL COLORS			BALDOR ELECTRIC Co.
REV. LTR: E	BY: JLP	REVISED: 01/19/99 10:15	TDR: 0171435
CD0005		FILE: AAA00005140	MDL: –
		MTL: –	3PH, DV, 9 LEADS