ABB BALDOR RELIANCE

Customer information packet

EM3711T-58

10HP, 2900RPM, 3PH, 50HZ, 215T, 3740M, TEFC, F1
Class - None
Division - Not Applicable

Copyright © All product information within this document is subject to ABB Motors and Mechanical Inc. copyright © protection, unless otherwise noted.
10/6/2026 7:37:00 PM

Specifications

Enclosure	TEFC
Frame	215T
Frame Material	Steel
Frequency	50.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	10.000 HP @ 50 HZ
Phase	3
Synchronous Speed @ Frequency	3000 RPM @ 50 HZ
Voltage @ Frequency	400.0 V @ 50 HZ
Agency Approvals	CE
	CSA
	CURUS
	IE3
	UKCA
	UR
	WEEE
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	13.100 A @ 400.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	90.2 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard

Part Detail

Revision	R
Type	AC
Mech. spec.	37A001
Base	
Status	PRD/A
Elec. spec.	37WGR698
Layout	37LYA001
Eff. date	11-05-2025
CD Diagram	CD0382
Poles	02
Leads	6#14
Proprietary	False
Created date	12-08-2014

Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	13.1 a
Insulation Class	F
Inverter Code	Inverter Ready
KVA Code	H
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	6 @ 14 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3740M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	19.01 IN
Power Factor	89
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.15
Shaft Diameter	1.375 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	2900 rpm
Speed Code	Single Speed
Starting Method	Wye Start - Delta Run
Thermal Device - Bearing	None
Thermal Device - Winding	None

Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3444L									
CAT NO	EM3711T-58								
SPEC.	37A001R698G1								
HP	10/7.5KW				**PH**	3			
VOLTS	400								
AMP	13.1								
RPM	2900 1/MIN IP54 IC411 64KG								
FRAME	215T	**HZ**	50			**I.P.**	44		
SER.F.	1.15	**CODE**	H	**DES**	B	**CL**	F		
NOM.EFF.	90.2								
PF	89			**USABLE AT 208V**		N/A			
RATING	40C AMB-S1 CONT				**CC**				
DE BRG	6307		**ODE**	6206					
ENCL	TEFC	**SN**							
VPWM INVERTER READY									
CT5-50(10:1)VT2.5-50(20:1									
BLANK	IE3-93.2(75%)93.7(50%)								

AC Induction Motor Performance Data
Record # 48453
Typical performance - not guaranteed values

Winding: 37WGR698-R001	**Type:** 3740M	**Enclosure:** TEFC

Nameplate Data				**400 V, 50 Hz: Single Voltage Motor**	
Rated Output (HP)			10	**Full Load Torque**	18 LB-FT
Volts			400	**Start Configuration**	direct on line
Full Load Amps			13.1	**Breakdown Torque**	63.8 LB-FT
R.P.M.			2900	**Pull-up Torque**	33.2 LB-FT
Hz	50	**Phase**	3	**Locked-rotor Torque**	38.4 LB-FT
NEMA Design Code	B	**KVA Code**	H	**Starting Current**	99.1 A
Service Factor (S.F.)			1.15	**No-load Current**	4.38 A
NEMA Nom. Eff.	90.2	**Power Factor**	89	**Line-line Res. @ 25ºC**	0.662 Ω
Rating - Duty			40C AMB-CONT	**Temp. Rise @ Rated Load**	79°C
S.F. Amps				**Temp. Rise @ S.F. Load**	97°C
				Locked-rotor Power Factor	35.3
				Rotor inertia	0.364 LB-FT2

Load Characteristics 400 V, 50 Hz, 10 HP

% of Rated Load	**25**	**50**	**75**	**100**	**125**	**150**	**S.F.**
Power Factor	54	76	86	89	90	91	90
Efficiency	91.4	93.7	93.2	92.5	90.9	89	91.5
Speed	2981	2957	2932	2905	2875	2840	2887
Line amperes	5.29	7.45	10	13.1	16.3	19.8	15

ABB Motors and Mechanical Inc.

WINDING # 37WGR698

10 HP 3 PH 50 HZ 2900 RPM 400 V 3740M

Typical performance - not guaranteed values.

TORQUES(LB-FT): PO=63.8 PU=33.2 LR=38.4 LRA=99.1




37LYA001
(717-735) = 17.89
(736-744) = 19.01
(745-750) = 19.76
(751-756) = 20.51
5.01
3.88
3.38
GREASE FITTING (EA. END)
.31 KEY 2.38 LONG
Ø10.28
Ø1.3750 1.3745
6 HOLES Ø.41
5.50
.50
7.00
3.50
8.00
Ø9.54
7.96
2.38
10.02
5.25
4.25
4.25
6.72
LEAD HOLE Ø1.38
9.50
CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT BALDOR'S PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION
REV. DESC: LOAD DRAWING TO SOLIDWORKS
REV: T
VERSION: 02
REVISED: 09:45:08 07/12/2022
TDR: 000001192990
MODEL NO. 37LYA001
REF: -
BY: ENALEM0
B
BALDOR
STD HORZ NEMA 213-215T TEFC 37M
37LYA001

CD0382



RUN CONNECTION
(1D)



LINE

START CONNECTION
(1Y)



LINE

NOTES:

1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.
5. FOR ACROSS–THE–LINE STARTING, USE 'RUN' CONNECTION.

CD0382

REV. DESC: ADD CLASS CONN00000007		
REV. LTR: F	VERSION: 01	TDR: 000001099922
FILE: \AAA\00005\243	REVISED: 09:05:32 02/19/2019	BY: ENBRIR0
MTL: –		

BALDOR - RELIANCE®

3PH, SV, 6 LEADS, Y START/D RUN

SH 1 of 1