ABB BALDOR RELIANCE

Customer information packet

EM4115T-8

50HP, 1775RPM, 3PH, 60HZ, 326T, 1266M, TEFC, F1
Class - None
Division - Not Applicable

Copyright © All product information within this document is subject to ABB Motors and Mechanical Inc. copyright © protection, unless otherwise noted.
11/18/2026 3:06:21 AM

Specifications

Enclosure	TEFC
Frame	326T
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	50.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	200.0 V @ 60 HZ
Agency Approvals	CURUSEEV
	NEMA PREMIUM
	NEMA PREMIUM (OLD LOGO)
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	129.000 A @ 208.0 V
	131.000 A @ 200.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	94.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	131.0 a

Part Detail

Revision	AL
Type	AC
Mech. spec.	12H13
Base	
Status	PRD/A
Elec. spec.	12WGX281
Layout	12LYH013
Eff. date	06-27-2024
CD Diagram	CD0695
Poles	04
Leads	6#6
Proprietary	False
Created date	01-01-0001

Insulation Class	F
Inverter Code	Inverter Ready
KVA Code	H
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	6 @ 6 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	1266M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	30.28 IN
Power Factor	87
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	2.125 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	1775 rpm
Speed Code	Single Speed
Starting Method	Part Winding
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3443L											
CAT.NO.	EM4115T-8			**CUST. P/N**						**ENCL**	TEFC
SPEC.	12H013X281G1	**CC**	010A	**FRAME**	326T		**SER.NO.**				
HP	50	**CLASS**	F	**HZ**	60						
R.P.M.	1775	**PH**	3	**DES**	B						
VOLTS	200	**CODE**	H	**ODE BRG**	6311	**DE BRG**	6312				
AMPS	131										
RATING	40C AMB-CONT	**NEMA NOM. EFF.**	94.5	**GREASE**	POLYREX EM						
P.F.	87	**SER.F.**	1.15	**VPWM INVERTER READY**							
HTR-VOLTS		**HTR-AMPS**		**HTR-WATTS**							

Accessories

Part number	Description	Multiplier
12-1105	C FACE KIT	A8
12EP1501A03SP	D-FLANGE KIT	A8

AC Induction Motor Performance Data
Record # 3432
Typical performance - not guaranteed values

Winding: 12WGX281-R001	**Type:** 1266M	**Enclosure:** TEFC

Nameplate Data				**200 V, 60 Hz: Single Voltage Motor**	
Rated Output (HP)			50	**Full Load Torque**	149 LB-FT
Volts			200	**Start Configuration**	direct on line
Full Load Amps			131	**Breakdown Torque**	446 LB-FT
R.P.M.			1775	**Pull-up Torque**	210 LB-FT
Hz	60	**Phase**	3	**Locked-rotor Torque**	229 LB-FT
NEMA Design Code	B	**KVA Code**	H	**Starting Current**	897 A
Service Factor (S.F.)			1.15	**No-load Current**	46.6 A
NEMA Nom. Eff.	94.5	**Power Factor**	87	**Line-line Res. @ 25ºC**	0.0211 Ω
Rating - Duty			40C AMB-CONT	**Temp. Rise @ Rated Load**	64°C
S.F. Amps				**Temp. Rise @ S.F. Load**	77°C
				Locked-rotor Power Factor	27
				Rotor inertia	8.79 LB-FT2

Load Characteristics 200 V, 60 Hz, 50 HP

% of Rated Load	**25**	**50**	**75**	**100**	**125**	**150**	**S.F.**
Power Factor	48	71	81	88	87	88	87
Efficiency	91.5	94.4	94.9	94.7	94.3	93.6	94.5
Speed	1795	1790	1784	1778	1773	1765	1775
Line amperes	62	82	107	131	165	197	151.4


ABB Motors and Mechanical Inc.


WINDING # 12WGX281

50 HP 3 PH 60 HZ 1775 RPM 200 V 1266M

TORQUES(LB-FT): PO=446 PU=210 LR=229 LRA=897


Typical performance - not guaranteed values.





12LYH013
[769]
(1232 - 1280) = 30.28
(1282 - 1288, 4 POLE ONLY)
[350]
13.78
[141]
5.56
[133]
5.25
NAMEPLATE
.50 [13] KEY
3.88 [99] LONG
[54]
54
Ø2.125
2.124
SLINGER
EA. END
(WHEN REQ'D)
DRAIN FITTING
(EA. END)
[267]
10.50
[267]
10.50
[25]
1.00
[305]
12.00
[133]
5.25
[356]
14.00
[455]
17.93
[371]
14.61
[215]
8.46
[82]
3.22
[412]
16.23
8.00
7.94
LEAD
HOLE
Ø2.50 [64]
[108]
4.25
[23]
.90
8 HOLES
Ø.66 [17]
[159]
6.25
[159]
6.25
[306]
12.07
[184]
7.25
[368]
14.50
CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT THE PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION
REV. DESC: ADD METRIC DIMENSIONS
REV: N
VERSION: 09
REVISED: 08:52:21 07/21/2026
TDR: 000001280594
MODEL NO. 12LYH013
REF: -
BY: ENNIND0
B
BALDOR - RELIANCE®
HOR TEFC 324-6T; HI-EFF
12LYH013

CD0695


TYPICAL WYE–CONNECTED MOTOR




START CONNECTION



RUN CONNECTION



TYPICAL DELTA–CONNECTED MOTOR



NOTES:

1. MOTOR MAY BE WYE CONNECTED OR DELTA CONNECTED.
2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
5. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

CD0695

REV. DESC: REVISE TO SHOW OPTIONAL COLORS			BALDOR ELECTRIC Co.
REV. LTR: C	BY: JLP	REVISED: 01/21/99 3:19	TDR: 0171435
CD0695		FILE: AAA00005151	MDL: –
		MTL: –	3PH, SV, 6 LEADS, PART WINDING START