

622012-011

RPM-AC VARIABLE SPEED ALTERNATING CURRENT MOTOR RL5024-DPFV

ENCLOSURE: OPEN DRIP PROOF
MOUNTING: F1, FOOT MOUNT

COOLING: FORCE-VENTILATED

65.51
32.00
17.98 TYP
FRAME LIFTING
N-W = 10.00
V = 9.75
8.0 K'WAY
1.00 K'WAY
M16-2.0 GROUND
CORE
12.60 TYP.
19.23
38.46
51.51
32.24
12.50 $\begin{smallmatrix} +.00 \\ -.09 \end{smallmatrix}$
4.01
1.08 TYP.
4.64 TYP.
10.00
20.00
24.74
45.93
Ø 4.500 $\begin{smallmatrix} +.000 \\ -.001 \end{smallmatrix}$
Ø 1.18 THRU (4) HOLES
GLAND PLATE

NOTES:
1. MOTOR WEIGHTS MAY VARY +/- 15%
2. SHAFT RUNOUT 0.003 T.I.R. MAX
3. DIMENSIONS ARE IN INCHES

CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT THE PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION

RL5024	4870	BALDOR-DODGE-RELIANCE PROPRIETARY & CONFIDENTIAL: THIS DRAWING IS THE PROPERTY OF BALDOR-DODGE-RELIANCE AND/OR ITS SUBSIDIARIES AND IS NOT TO BE USED, DUPLICATED OR DISCLOSED WITHOUT THE EXPRESS WRITTEN PERMISSION OF THE COMPANY.		REV. DESC: CORRECT SHAFT V DIMENSION TO 9.75		REV: A		VERSION: 01	REVISED: 09:38:10 01/27/2022	TDR: 000001185048
FRAME SIZE	WT (LBS)			MODEL NO. 622012-011		BY: USANBRO28		REF: -		

BALDOR - RELIANCE®

DIM SHEET, RL5024,FT. MNT,OVR SIZED F1 CBOX,4.500 SHAFT EXT

622012-011

622012-011

RPM-AC VARIABLE SPEED ALTERNATING CURRENT MOTOR RL5024-DPFV

ENCLOSURE: OPEN DRIP PROOF
MOUNTING: F1, FOOT MOUNT

COOLING: FORCE-VENTILATED

65.51
32.00
17.98 TYP
FRAME LIFTING
N-W = 10.00
V = 9.75
8.0 K'WAY
1.00 K'WAY
12.60 TYP.
19.23
8.50
38.46
51.51
CORE
M16-2.0 GROUND
32.24
12.50 $\begin{smallmatrix} +.00 \\ -.09 \end{smallmatrix}$
4.01
1.08 TYP.
4.64 TYP.
10.00
20.00
24.74
45.93
Ø 4.500 $\begin{smallmatrix} +.000 \\ -.001 \end{smallmatrix}$
Ø 1.18 THRU (4) HOLES
GLAND PLATE

NOTES:
1. MOTOR WEIGHTS MAY VARY +/- 15%
2. SHAFT RUNOUT 0.003 T.I.R. MAX
3. DIMENSIONS ARE IN INCHES

BALDOR-DODGE-RELIANCE PROPRIETARY & CONFIDENTIAL:
THIS DRAWING IS THE PROPERTY OF BALDOR-DODGE-RELIANCE
AND/OR ITS SUBSIDIARIES AND IS NOT TO BE USED, DUPLICATED
OR DISCLOSED WITHOUT THE EXPRESS WRITTEN PERMISSION
OF THE COMPANY.

RL5024	4870
FRAME SIZE	WT (LBS)

REV. DESC: CORRECT SHAFT V DIMENSION TO 9.75			
REV: A	VERSION: 01	REVISED: 09:38:10 01/27/2022	TDR: 000001185048
MODEL NO. 622012-011			REF: -
BY: USANBRO28			

CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT THE PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION

BALDOR - RELIANCE®

DIM SHEET, RL5024,FT. MNT,OVR SIZED F1 CBOX,4.500 SHAFT EXT

622012-011

622012-011

RPM-AC VARIABLE SPEED ALTERNATING CURRENT MOTOR
RL5024-DPFV

ENCLOSURE: OPEN DRIP PROOF
MOUNTING: F1, FOOT MOUNT

COOLING: FORCE-VENTILATED

65.51
32.00
17.98 TYP
FRAME LIFTING
N-W = 10.00
V = 9.75
8.0 K'WAY
1.00 K'WAY
12.60 TYP.
19.23
8.50
38.46
51.51
CORE
M16-2.0 GROUND
32.24
12.50 $\begin{smallmatrix} +.00 \\ -.09 \end{smallmatrix}$
4.01
1.08 TYP.
4.64 TYP.
10.00
20.00
24.74
45.93
GLAND PLATE
 $\phi 1.18$ THRU (4) HOLES
 $\phi 4.500 \begin{smallmatrix} +.000 \\ -.001 \end{smallmatrix}$

NOTES:
1. MOTOR WEIGHTS MAY VARY +/- 15%
2. SHAFT RUNOUT 0.003 T.I.R. MAX
3. DIMENSIONS ARE IN INCHES

BALDOR-DODGE-RELIANCE PROPRIETARY & CONFIDENTIAL:
THIS DRAWING IS THE PROPERTY OF BALDOR-DODGE-RELIANCE
AND/OR ITS SUBSIDIARIES AND IS NOT TO BE USED, DUPLICATED
OR DISCLOSED WITHOUT THE EXPRESS WRITTEN PERMISSION
OF THE COMPANY.

REV. DESC: CORRECT SHAFT V DIMENSION TO 9.75
REV: A VERSION: 01 REVISED: 09:38:10 01/27/2022 TDR: 000001185048
MODEL NO. 622012-011 REF: -
BY: USANBRO28

CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT THE PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION

BALDOR - RELIANCE®
DIM SHEET, RL5024,FT. MNT,OVR SIZED F1 CBOX,4.500 SHAFT EXT

RL5024 4870
FRAME SIZE WT (LBS)

622012-011

622012-011

RPM-AC VARIABLE SPEED ALTERNATING CURRENT MOTOR
RL5024-DPFV

ENCLOSURE: OPEN DRIP PROOF
MOUNTING: F1, FOOT MOUNT

COOLING: FORCE-VENTILATED

65.51
32.00
17.98 TYP
FRAME LIFTING
N-W = 10.00
V = 9.75
8.0 K'WAY
1.00 K'WAY
12.60 TYP.
19.23
8.50
38.46
51.51
CORE
M16-2.0 GROUND
32.24
12.50 $\begin{smallmatrix} +.00 \\ -.09 \end{smallmatrix}$
4.01
1.08 TYP.
4.64 TYP.
10.00
20.00
24.74
45.93
GLAND PLATE
 $\phi 1.18$ THRU (4) HOLES
 $\phi 4.500 \begin{smallmatrix} +.000 \\ -.001 \end{smallmatrix}$

NOTES:
1. MOTOR WEIGHTS MAY VARY +/- 15%
2. SHAFT RUNOUT 0.003 T.I.R. MAX
3. DIMENSIONS ARE IN INCHES

BALDOR-DODGE-RELIANCE PROPRIETARY & CONFIDENTIAL:
THIS DRAWING IS THE PROPERTY OF BALDOR-DODGE-RELIANCE
AND/OR ITS SUBSIDIARIES AND IS NOT TO BE USED, DUPLICATED
OR DISCLOSED WITHOUT THE EXPRESS WRITTEN PERMISSION
OF THE COMPANY.

REV. DESC: CORRECT SHAFT V DIMENSION TO 9.75
REV: A VERSION: 01 REVISED: 09:38:10 01/27/2022 TDR: 000001185048
MODEL NO. 622012-011 REF: -
BY: USANBRO28

CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT THE PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION

BALDOR - RELIANCE®
DIM SHEET, RL5024,FT. MNT,OVR SIZED F1 CBOX,4.500 SHAFT EXT

RL5024 4870
FRAME SIZE WT (LBS)

622012-011

622012-011

RPM-AC VARIABLE SPEED ALTERNATING CURRENT MOTOR RL5024-DPFV

ENCLOSURE: OPEN DRIP PROOF
MOUNTING: F1, FOOT MOUNT

COOLING: FORCE-VENTILATED

65.51
32.00
17.98 TYP
FRAME LIFTING
N-W = 10.00
V = 9.75
8.0 K'WAY
1.00 K'WAY
12.60 TYP.
19.23
8.50
38.46
51.51
CORE
M16-2.0 GROUND
32.24
12.50 ^{+0.00} _{-.09}
4.01
1.08 TYP.
4.64 TYP.
10.00
20.00
24.74
45.93
Ø 4.500 ^{+0.000} _{-.001}
Ø 1.18 THRU (4) HOLES
GLAND PLATE

NOTES:
1. MOTOR WEIGHTS MAY VARY +/- 15%
2. SHAFT RUNOUT 0.003 T.I.R. MAX
3. DIMENSIONS ARE IN INCHES

CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT THE PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION

RL5024	4870	BALDOR-DODGE-RELIANCE PROPRIETARY & CONFIDENTIAL: THIS DRAWING IS THE PROPERTY OF BALDOR-DODGE-RELIANCE AND/OR ITS SUBSIDIARIES AND IS NOT TO BE USED, DUPLICATED OR DISCLOSED WITHOUT THE EXPRESS WRITTEN PERMISSION OF THE COMPANY.		REV. DESC: CORRECT SHAFT V DIMENSION TO 9.75		REV: A		VERSION: 01	REVISED: 09:38:10 01/27/2022	TDR: 000001185048
FRAME SIZE	WT (LBS)			MODEL NO. 622012-011		BY: USANBRO28		REF: -		

BALDOR - RELIANCE®

DIM SHEET, RL5024,FT. MNT,OVR SIZED F1 CBOX,4.500 SHAFT EXT

622012-011