ABB BALDOR RELIANCE

# Customer information packet

## L3514TM

1.5HP, 1725RPM, 1PH, 60HZ, 145T, 3532LC, TEFC
Class - None
Division - Not Applicable

Copyright © All product information within this document is subject to ABB Motors and Mechanical Inc. copyright © protection, unless otherwise noted.
11/19/2026 12:05:59 AM

## Specifications

| | |
|---|---|
| **Enclosure** | TEFC |
| **Frame** | 145T |
| **Frame Material** | Steel |
| **Frequency** | 60.00 Hz |
| **Haz Area Class and Group** | None |
| **Haz Area Division** | Not Applicable |
| **Motor Letter Type** | Cap Start, Cap Run |
| **Output @ Frequency** | 1.500 HP @ 60 HZ |
| **Phase** | 1 |
| **Synchronous Speed @ Frequency** | 1800 RPM @ 60 HZ |
| **Voltage @ Frequency** | 115.0 V @ 60 HZ |
| | 208.0 V @ 60 HZ |
| | 230.0 V @ 60 HZ |
| **Agency Approvals** | C UR US |
| **Ambient Temperature** | 40 °C |
| **Auxiliary Box** | NO AUXILLARY BOX |
| **Auxiliary Box Lead Termination** | None |
| **Base Indicator** | Rigid |
| **Bearing Grease Type** | Polyrex EM (-20F +300F) |
| **Blower** | None |
| **Current @ Voltage** | 12.200 A @ 115.0 V |
| | 5.500 A @ 230.0 V |
| | 6.200 A @ 208.0 V |
| **Design Code** | L |
| **Drip Cover** | No Drip Cover |
| **Duty Rating** | CONT |
| **Efficiency @ 100% Load** | 80.0 % |
| **Electrically Isolated Bearing** | Not Electrically Isolated |
| **Feedback Device** | NO FEEDBACK |
| **Front Shaft Indicator** | None |
| **Heater Indicator** | No Heater |
| **High Voltage Full Load Amps** | 5.5 a |

## Part Detail

| | |
|---|---|
| **Revision** | D |
| **Type** | AC |
| **Mech. spec.** | 35HH612 |
| **Base** | |
| **Status** | PRD/A |
| **Elec. spec.** | 35WGG398 |
| **Layout** | 35LYHH612 |
| **Eff. date** | 06-19-2025 |
| **CD Diagram** | CD0016A02 |
| **Poles** | 04 |
| **Leads** | 7#18,1#16 #4TH |
| **Proprietary** | False |
| **Created date** | 02-23-2023 |

| | |
|---|---|
| **Insulation Class** | F |
| **Inverter Code** | Not Inverter |
| **KVA Code** | H |
| **Lifting Lugs** | No Lifting Lugs |
| **Locked Bearing Indicator** | No Locked Bearing |
| **Motor Lead Quantity/Wire Size** | 7 @ 18 AWG |
| **Motor Lead Termination** | Flying Leads |
| **Motor Standards** | NEMA |
| **Motor Type** | 3532LC |
| **Mounting Arrangement** | F1 |
| **Number of Poles** | 4 |
| **Overall Length** | 14.16 IN |
| **Power Factor** | 90 |
| **Product Family** | General Purpose |
| **Pulley End Bearing Type** | Ball |
| **Pulley Face Code** | Standard |
| **Pulley Shaft Indicator** | Standard |
| **Rodent Screen** | None |
| **RoHS Status** | ROHS COMPLIANT |
| **Service Factor** | 1.00 |
| **Shaft Diameter** | 0.875 IN |
| **Shaft Ground Indicator** | No Shaft Grounding |
| **Shaft Rotation** | Reversible |
| **Shaft Slinger Indicator** | No Slinger |
| **Speed** | 1725 rpm |
| **Speed Code** | Single Speed |
| **Starting Method** | Direct on line |
| **Thermal Device - Bearing** | None |
| **Thermal Device - Winding** | None |
| **Vibration Sensor Indicator** | No Vibration Sensor |
| **Winding Thermal 1** | Manual Thermal Overload |
| **Winding Thermal 1 Location** | SB |
| **Winding Thermal 2** | None |

**Nameplate**

| NP1257L | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| **CAT.NO.** | L3514TM | | | | | | | | | | |
| **SPEC.** | 35HH612G398 | | | | | | | | | | |
| **HP** | 1.5 | | | | | | | | | | |
| **VOLTS** | 115/208-230 | | | | | | | | | | |
| **AMP** | 12.2/6.2-5.5 | | | | | | | | | | |
| **RPM** | 1725 | | | | | | | | | | |
| **FRAME** | 145T | | **HZ** | 60 | | **PH** | 1 | | | | |
| **SER.F.** | 1.00 | **CODE** | H | **DES** | L | **CL** | F | | | | |
| **NEMA-NOM-EFF** | 80 | **PF** | 90 | | | | | | | | |
| **RATING** | 40C AMB-CONT | | | | | | | | | | |
| **CC** | | | | | | | | | | | |
| **DE** | 6205 | **ODE** | 6203 | | | | | | | | |
| **ENCL** | TEFC | **SN** | | | | | | | | | |

**Accessories**

| Part number | Description | Multiplier |
|---|---|---|
| 35-8762 | C FACE KIT | A8 |
| 35EP1506A01SP | D-FLANGE KIT | A8 |

**AC Induction Motor Performance Data**
Record # 89151
Typical performance - not guaranteed values

| **Winding:** 35WGG398-R001 | **Type:** 3532LC | **Enclosure:** TEFC |
|---|---|---|

| **Nameplate Data** | | | | **230 V, 60 Hz: High Voltage Connection** | |
|---|---|---|---|---|---|
| **Rated Output (HP)** | | | 1.5 | **Full Load Torque** | 4.56 LB-FT |
| **Volts** | | | 115/208-230 | **Start Configuration** | direct on line |
| **Full Load Amps** | | | 13.4/6.8-6.7 | **Breakdown Torque** | 9.9 LB-FT |
| **R.P.M.** | | | 1725 | **Pull-up Torque** | 8.06 LB-FT |
| **Hz** | 60 | **Phase** | 1 | **Locked-rotor Torque** | 12.98 LB-FT |
| **NEMA Design Code** | L | **KVA Code** | H | **Starting Current** | 43.97 A |
| **Service Factor (S.F.)** | | | 1 | **No-load Current** | 0.877 A |
| **NEMA Nom. Eff.** | 80 | **Power Factor** | 90 | **Line-line Res. @ 25ºC** | 0.517 Ω A Ph<br>1.32 Ω B Ph |
| **Rating - Duty** | | | 40C AMB-CONT | **Temp. Rise @ Rated Load** | 67°C |
| | | | | **Locked-rotor Power Factor** | 91.1 |
| | | | | **Rotor inertia** | 0.232 lb-ft² |

**Load Characteristics 230 V, 60 Hz, 1.5 HP**

| **% of Rated Load** | **25** | **50** | **75** | **100** | **125** | **150** |
|---|---|---|---|---|---|---|
| **Power Factor** | 95 | 98 | 98 | 98 | 97 | 96 |
| **Efficiency** | 68.1 | 80.4 | 82.5 | 81.1 | 76.9 | 69.8 |
| **Speed** | 1782 | 1765 | 1746 | 1723 | 1690 | 1641 |
| **Line amperes** | 1.83 | 3.08 | 4.5 | 6.1 | 8.12 | 10.79 |


ABB Motors and Mechanical Inc.

WINDING # 35WGG398


1.5 HP 1 PH 60 HZ 1725 RPM 230 V 3532LC

Typical performance - not guaranteed values.


TORQUES(LB-FT): PO=9.9 PU=8.06 LR=12.98 LRA=43.97




11/19/2026 ACPERF, record # 89151


35LYHH612
510-528 = 13.29
529-535 = 14.16
536-546 = 15.54
3.76
GREASE FITTINGS EACH END
2.50
2.25
Ø7.19
.19 KEY
1.38 LONG
NAMEPLATE
Ø.8750
Ø.8745
4.00
2.25
6 HOLES
Ø.34
5.00
.50
5.94
6.61
5.75
4.28
2.27
MANUAL
THERMAL
W/BOOT
6.77
3.50
3.44
LEAD HOLE
Ø1.09
2.75
2.75
4.63
3.25
6.50
CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT THE PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION
REV. DESC: UPDATE 3D MODEL BOM PER REV C, NO CHG TO 2D PRINT
REV: C
VERSION: 03
REVISED: 08:50:58 03/28/2022
TDR: 000001187751
MODEL NO. 35LYHH612
REF: -
BY: USBUFRA
B
BALDOR - RELIANCE®
STD HORZ 143-5T TEFC 35LC W/1" MTO & 1.09 DIA. LEAD HOLE
SH 1 OF 1
35LYHH612

CD0016A02




| | LINE A | LINE B | JOIN | JOIN | JOIN |
|---|---|---|---|---|---|
| HIGH STD | 1 | 4 | 2,3 | 8,9 | J,5 |
| HIGH OPP | 1 | 4 | 2,3 | 5,9 | J,8 |
| LOW STD | 1,3 | 4 | 8,9 | 2,J,5 | – |
| LOW OPP | 1,3 | 4 | 5,9 | 2,J,8 | – |

NOTES:

1. STANDARD ROTATION IS CCW FACING END OPPOSITE SHAFT EXTENSION.
2. MULTIPLE CAPACITORS ARE CONNECTED IN PARALLEL UNLESS OTHERWISE SPECIFIED.
3. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

| | | | |
|---|---|---|---|
| REV. DESC: REMOVE OPTIONAL THERMAL CONNECTION | | | BALDOR ELECTRIC Co. |
| REV. LTR: F | VERSION: 01 | TDR: 000000373039 | |
| CD0016A02 | FILE: \AAA\00007\411 | REVISED: 10:13:25 08/11/2005 | TYPE LC, DV, REV, OIL CAP ACR. LINE, THERMAL, 8 LEADS |
| | MTL: – | BY: ENJOEP0 | |

CD0016A02