# Customer information packet

## VEJMM3218T-5

5HP, 1750RPM, 3PH, 60HZ, 184JM, 3632M, ODTF, F1
Class - None
Division - Not Applicable

Copyright © All product information within this document is subject to ABB Motors and Mechanical Inc. copyright © protection, unless otherwise noted.
11/18/2026 12:08:03 PM

## Specifications

| | |
|---|---|
| **Enclosure** | ODTF |
| **Frame** | 184JM |
| **Frame Material** | Steel |
| **Frequency** | 60.00 Hz |
| **Haz Area Class and Group** | None |
| **Haz Area Division** | Not Applicable |
| **Motor Letter Type** | Three Phase |
| **Output @ Frequency** | 5.000 HP @ 60 HZ |
| **Phase** | 3 |
| **Synchronous Speed @ Frequency** | 1800 RPM @ 60 HZ |
| **Voltage @ Frequency** | 575.0 V @ 60 HZ |
| **Agency Approvals** | UR |
| | CSA |
| | CSA EEV |
| **Ambient Temperature** | 40 °C |
| **Auxiliary Box** | NO AUXILLARY BOX |
| **Auxiliary Box Lead Termination** | None |
| **Base Indicator** | No Mounting |
| **Bearing Grease Type** | Polyrex EM (-20F +300F) |
| **Blower** | None |
| **Current @ Voltage** | 5.200 A @ 575.0 V |
| **Design Code** | B |
| **Drip Cover** | Drip Cover |
| **Duty Rating** | CONT |
| **Efficiency @ 100% Load** | 89.5 % |
| **Electrically Isolated Bearing** | Not Electrically Isolated |
| **Feedback Device** | NO FEEDBACK |
| **Front Face Code** | Standard |
| **Front Shaft Indicator** | None |
| **Heater Indicator** | No Heater |
| **High Voltage Full Load Amps** | 5.2 a |
| **Insulation Class** | F |

## Part Detail

| | |
|---|---|
| **Revision** | P |
| **Type** | AC |
| **Mech. spec.** | 36N072 |
| **Base** | |
| **Status** | PRD/A |
| **Elec. spec.** | 36WGT160 |
| **Layout** | 36LYN072 |
| **Eff. date** | 04-20-2026 |
| **CD Diagram** | CD0006 |
| **Poles** | 04 |
| **Leads** | 3#16 |
| **Proprietary** | False |
| **Created date** | 01-01-0001 |

| | |
|---|---|
| **Inverter Code** | Inverter Ready |
| **KVA Code** | K |
| **Lifting Lugs** | No Lifting Lugs |
| **Locked Bearing Indicator** | Locked Bearing |
| **Motor Lead Exit** | Ko Box |
| **Motor Lead Quantity/Wire Size** | 3 @ 16 AWG |
| **Motor Lead Termination** | Flying Leads |
| **Motor Standards** | NEMA |
| **Motor Type** | 3632M |
| **Mounting Arrangement** | F1 |
| **Number of Poles** | 4 |
| **Overall Length** | 18.06 IN |
| **Power Factor** | 80 |
| **Product Family** | General Purpose |
| **Pulley End Bearing Type** | Ball |
| **Pulley Face Code** | C-Face |
| **Pulley Shaft Indicator** | Tapped & Key |
| **Rodent Screen** | None |
| **Service Factor** | 1.15 |
| **Shaft Diameter** | 0.875 IN |
| **Shaft Extension Location** | Pulley End |
| **Shaft Ground Indicator** | No Shaft Grounding |
| **Shaft Rotation** | Reversible |
| **Shaft Slinger Indicator** | Shaft Slinger |
| **Speed** | 1750 rpm |
| **Speed Code** | Single Speed |
| **Starting Method** | Direct on line |
| **Thermal Device - Bearing** | None |
| **Thermal Device - Winding** | None |
| **Vibration Sensor Indicator** | No Vibration Sensor |
| **Winding Thermal 1** | None |
| **Winding Thermal 2** | None |

**Nameplate**

| NP1259L | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| **CAT.NO.** | VEJMM3218T-5 | | | | | | | | | |
| **SPEC.** | 36N072T160E7 | | | | | | | | | |
| **HP** | 5 | | | | | | | | | |
| **VOLTS** | 575 | | | | | | | | | |
| **AMP** | 5.2 | | | | | | | | | |
| **RPM** | 1750 | | | | | | | | | |
| **FRAME** | 184JM | **HZ** | 60 | | **PH** | 3 | | | | |
| **SER.F.** | 1.15 | **CODE** | K | **DES** | B | **CL** | F | | | |
| **NEMA-NOM-EFF** | 89.5 | **PF** | 80 | | | | | | | |
| **RATING** | 40C AMB-CONT | | | | | | | | | |
| **CC** | 010A | | | | | | | | | |
| **DE** | 6207 | **ODE** | 6205 | | | | | | | |
| **ENCL** | ODTF | **SN** | | | | | | | | |
| | INVERTER DUTY 20:1 VT | | | | | | | | | |

**AC Induction Motor Performance Data**
Record # 10605
Typical performance - not guaranteed values

| **Winding:** 36WGT160-R001 | **Type:** 3632M | **Enclosure:** OPSB |
|---|---|---|

| **Nameplate Data** | | | | **575 V, 60 Hz: Single Voltage Motor** | |
|---|---|---|---|---|---|
| **Rated Output (HP)** | | | 5 | **Full Load Torque** | 15 LB-FT |
| **Volts** | | | 575 | **Start Configuration** | direct on line |
| **Full Load Amps** | | | 5.2 | **Breakdown Torque** | 51 LB-FT |
| **R.P.M.** | | | 1750 | **Pull-up Torque** | 30 LB-FT |
| **Hz** | 60 | **Phase** | 3 | **Locked-rotor Torque** | 37 LB-FT |
| **NEMA Design Code** | B | **KVA Code** | K | **Starting Current** | 40 A |
| **Service Factor (S.F.)** | | | 1.15 | **No-load Current** | 2.6 A |
| **NEMA Nom. Eff.** | 89.5 | **Power Factor** | 80 | **Line-line Res. @ 25ºC** | 4.6 Ω |
| **Rating - Duty** | | | 40C AMB-CONT | **Temp. Rise @ Rated Load** | 41°C |
| **S.F. Amps** | | | | **Temp. Rise @ S.F. Load** | 51°C |
| | | | | **Locked-rotor Power Factor** | 56 |
| | | | | **Rotor inertia** | 0.297 LB-FT2 |

**Load Characteristics 575 V, 60 Hz, 5 HP**

| **% of Rated Load** | **25** | **50** | **75** | **100** | **125** | **150** | **S.F.** |
|---|---|---|---|---|---|---|---|
| **Power Factor** | 38 | 60 | 73 | 80 | 83 | 86 | 0 |
| **Efficiency** | 88 | 91.3 | 91.6 | 90.7 | 89.5 | 88 | 0 |
| **Speed** | 1788 | 1777 | 1767 | 1754 | 1740 | 1726 | 0 |
| **Line amperes** | 2.9 | 3.5 | 4.2 | 5.2 | 6.3 | 7.5 | 5.8 |


ABB Motors and Mechanical Inc.

WINDING # 36WGT160


5 HP 3 PH 60 HZ 1750 RPM 575 V 3632M

Typical performance - not guaranteed values.

TORQUES(LB-FT): PO=51 PU=30 LR=37 LRA=40






11/18/2026 ACPERF, record # 10605


36LYN072
614-623 = 16.67
624-634 = 18.04
635-646 = 19.54
4.25
CHECK W/GAUGE T-9038
2.890
2.860
.640
.610
(635-646) ONLY
GREASE FITTING (EACH END)
.13
.19 KEY
1.38 LONG
1 HOLE
.38-16 CL 3 TAP
.88 DEEP
R.H. THD'S
Ø8.60
NAMEPLATE
Ø6.54
Ø 4.500
4.497
Ø 1.0000
.9995
Ø .8745
.8740
Ø 1.250
1.248
SLINGER
4.27
Ø7.87
6.75
45°
45°
6.31
LEAD HOLE Ø1.09
4 HOLES .38-16 TAP ON Ø5.88 B.C.
5.68
CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT THE PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION
REV. DESC: LOAD OF 2D TO 3D CONVERSION FROM INOPC - PKG 37
REV: N
VERSION: 04
REVISED: 02:03:02 09/23/2019
TDR: 000001120280
MODEL NO. 36LYN072
REF: -
BY: ENBILT0
B
BALDOR - RELIANCE®
STD VERT 182-4JM ODTF 36M W/DRIP COVER
36LYN072


CD0006

TYPICAL WYE–CONNECTED MOTOR




TYPICAL DELTA–CONNECTED MOTOR




NOTES:

1. THREE LEAD MOTOR MAY BE EITHER WYE CONNECTED OR DELTA CONNECTED.
2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
5. LEAD COLORS ARE OPTIONAL. LEADS MUST BE NUMBERED AS SHOWN.

CD0006

| | | | |
|---|---|---|---|
| REV. DESC: ADD CLASS CONN00000007 | | | BALDOR - RELIANCE® |
| REV. LTR: E | VERSION: 01 | TDR: 000001099922 | |
| FILE: \AAA\00005\141 | REVISED: 10:24:49 02/19/2019 | BY: ENBRIR0 | 3PH, SV, 3 LEADS, WYE OR DELTA CONNECTED |
| MTL: – | | | SH 1 of 1 |