

ABB BALDOR RELIANCE III

Customer information packet

VL1323A

3HP, 3450RPM, 1PH, 60HZ, 56C, 3535LC, OPEN, F1

Class -

Division - Not Applicable

Specifications

Enclosure	ODP
Frame	56C
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Division	Not Applicable
Output @ Frequency	3.000 HP @ 60 HZ
Phase	1
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ
Agency Approvals	UR
	CSA
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	No Mounting
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	13.000 A @ 230.0 V
Design Code	L
Drip Cover	Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	82.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Terminal Panel
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	13.0 a
Insulation Class	B
Inverter Code	Not Inverter
KVA Code	K
Lifting Lugs	No Lifting Lugs

Part Detail

Revision	AN
Type	AC
Mech. spec.	35H993
Base	
Status	NLA/A
Elec. spec.	35WGY105
Layout	35LYH993
Eff. date	04-10-2015
CD Diagram	CD0225
Poles	02
Leads	2#14 A PH,3#18 B&J
Proprietary	False
Created date	06-22-2007

Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Terminal Panel
Motor Lead Quantity/Wire Size	2 @ 14 AWG, A PH
Motor Lead Termination	None
Motor Standards	NEMA
Motor Type	3535LC
Mounting Arrangement	F1
Number of Poles	2
Overall Length	13.63 IN
Power Factor	93
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.15
Shaft Diameter	0.625 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible: Connected OPP STD
Shaft Slinger Indicator	No Slinger
Speed	3450 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Do Not Use Eve-Not Valid
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	Automatic Thermal Overload
Winding Thermal 1 Location	SB
Winding Thermal 2	None

Nameplate

NP1257L											
CAT.NO.											
SPEC.	35H993Y105										
HP	3										
VOLTS	230										
AMP	13										
RPM	3450										
FRAME	56C				HZ		60		PH		1
SER.F.	1.15	CODE	K	DES		L	CL	B			
NEMA-NOM-EFF	82.5	PF	93								
RATING	40C AMB-CONT										
CC											
DE	6205	ODE	6203								
ENCL	OPEN	SN									

AC Induction Motor Performance Data

Record # 10140

Typical performance - not guaranteed values

Winding: 35WGY105-R001			Type: 3535LC		Enclosure: OPEN	
Nameplate Data			230 V, 60 Hz: Single Voltage Motor			
Rated Output (HP)		3	Full Load Torque		4.5 LB-FT	
Volts		230	Start Configuration		direct on line	
Full Load Amps		13	Breakdown Torque		15.5 LB-FT	
R.P.M.		3450	Pull-up Torque		13 LB-FT	
Hz	60	Phase	1	Locked-rotor Torque		13 LB-FT
NEMA Design Code	L	KVA Code	K	Starting Current		108 A
Service Factor (S.F.)		1.15		No-load Current		5 A
NEMA Nom. Eff.	82.5	Power Factor	93	Line-line Res. @ 25°C		0.614 Ω A Ph 2.53 Ω B Ph
Rating - Duty		40C	AMB-CONT	Temp. Rise @ Rated Load		49°C
S.F. Amps				Temp. Rise @ S.F. Load		62°C

Load Characteristics 230 V, 60 Hz, 3 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	72	85	90	93	94	94	0
Efficiency	68.5	78.5	82	82.5	82.5	81	0
Speed	3578	3556	3535	3517	3487	3450	0
Line amperes	6	7.9	10.3	13	16	19	14.8

ABB Motors and Mechanical Inc.

WINDING # 35WGY105

Typical performance - not guaranteed values.

3 HP 1 PH 60 HZ 3450 RPM 230 V 3535LC

TORQUES (LB-FT): PO=15.5 PU=13 LR=13 LRA=108





