

# Motor Mod Express®

Modification Number	Motor Mod Express®	Page No.
<b>Balance</b>	.....	303
M1A	Dynamic Balance of Rotors	
<b>Bearings</b>	.....	303
M2A	Sealed Bearings	
M2B	Ball to Roller 1800 RPM or Below	
M2F	Add Isolated Bearings NEMA 254T through 5810 (SKF Insocoat or equivalent)	
<b>Brake Motors</b>	.....	305
M3D	Change Stearns Brake	
<b>Conduit Box</b>	.....	305
M4A	Tap or Provide Additional Lead Hole	
M4B	Rotate Conduit Box Lead Opening	
M4F	Replace Die Cast Aluminum Conduit Box	
M4G	Add Conduit Box for Thermostat or Heater Leads	
<b>Cord</b>	.....	307
M5A	Install Line Cord in Conduit Box or Terminal Panel	
M5B	Install 6 Foot, 3 Conductor, Type SO Cord	
<b>Drains</b>	.....	308
M7A	Add Condensation Drain Holes	
M7C	Close Standard Condensation Drain Holes	
M7D	Add Breather Drain to Cast Iron Explosion-Proof Motors	
<b>Dripcovers</b>	.....	309
M8A	Install Dripcover on TEFC or ODP	
<b>Leads</b>	.....	309
M10B	Reconnect from Nine Leads to Three Leads	
M10D	Longer Leads	
<b>Lubrication</b>	.....	310
M11A	Install Low Temperature Bearing Lubricant	
M11B	Add High Temperature Grease	
<b>Seals</b>	.....	311
M12A	Install Oil Seals	
M12B	Install Inpro/Seal®	
M12C	Install V-Ring Seals to Motor	
<b>Mountings</b>	.....	312
M13A	Add Rigid Base	
M13B	Install NEMA C-Face - Steel Band Construction	
M13C-1	Install NEMA C-Face - Cast Iron Construction	
M13C-2	Install NEMA C-Face – IEEE 841 Motors	
M13D	Add D-Flange	
M13E	Remove Rigid Base From Foot Mounted Steel Band Motors	
M13F-1	Convert Mounting Configuration for Steel Band Motor	
M13F-2	Convert Mounting Configuration for Cast Iron Motor	
M13G	Install NEMA C Face to Explosion-Proof Motors	
M13I	Labor only to mount grinder or buffer onto a pedestal and package for shipment	
<b>Mounting Diagrams</b>	.....	316
<b>Export Packaging</b>	.....	317
M14A	Open Crate Packaging	
M14B	Totally Enclosed Crate Packaging	
M14C	Motor and Nameplate Photograph	

## Motor Mod Express®

Modification Number	Motor Mod Express®	Page No.
<b>Nameplate</b>	.....	318
M15A	Provide Original Nameplate for Remote Mounting	
M15B	Replace Nameplate	
M15C	Laser Engrave Nameplate into Stainless Steel Motor	
M15E	Mail Nameplates to Customer	
M15F	Mark Nameplate with CE	
<b>Blowers</b>	.....	318
M16A	Add Constant Velocity Blower Unit	
M16B	Convert from a Three Phase to a Single Phase Blower	
<b>Paint</b>	.....	319
M17A	Paint Motor to Baldor-Reliance® Stock Paint Color	
M17B	Paint Motor or Parts to Customer Specified Color	
<b>Lifting Lugs</b>	.....	319
M18A	Add Lifting Lugs up to a 326T Frame Size	
<b>Hardware</b>	.....	320
M20A	Exchange Plated Hardware for Stainless Steel	
<b>Space Heaters</b>	.....	320
M21A	Add Space Heaters to TEFC or Open Motors	
<b>Thermal Protectors</b>	.....	321
M23A	Thermostats	
<b>Thermocouples</b>	.....	321
M24A	Iron Constantan	
<b>Thermistors</b>	.....	322
M25A	Thermistors	
<b>Tropicalization</b>	.....	322
M26A	Protection of Windings and Mechanical Parts	
<b>Weatherproofing</b>	.....	322
M27A	Treatment of Windings and Mechanical Parts	
<b>Shaft Modifications</b>	.....	323
M29A	Drill and Tap or Flat	
M29B	Convert from TEFC to TEAO	
M29C	Threading	
M29D	Convert "T" Frame to "U" Frame Shaft Dimension or Smaller (TS)	
M29F	Shorten Shafts without Reducing the Overall Dimension	
<b>Tach and Encoder Mounting Kits</b>	.....	325
M31D	Add Encoder Kit to Inverter Duty V*S Master or RPMAC Motor	
M31E	Additional Mounted Encoder Option for IDRPM Motors	
<b>Testing</b>	.....	326
M32A	Performance Testing Per IEEE 112	
M33A	Short Motor Test	
M33B	Routine Motor Test	
M33C	Complete Motor Test	
M33D	Calibration Test	
M33E	Sound Measurement Test	
<b>Terminal Blocks (50 Hz, 3 Phase Motors Only)</b>	.....	328
M35A	Install Terminal Blocks in Conduit Box and Connect Leads	

## Motor Mod Express®

Modification Number	Motor Mod Express®	Page No.
<b>Starters</b>	.....	329
M36A	Add Magnetic or Manual Starter to Grinder or Buffer – Starter – Single Phase	
M36B	Add Magnetic or Manual Starter to Grinder or Buffer – Starter – Three Phase	
M36C	Add Magnetic or Manual Starter to Grinder or Buffer – Magnetic Starter – Three Phase	
M36D	Overload Protection for Dust Control Unit	
<b>Shaft Grounding</b>	.....	331
M39A	Shaft Grounding Systems	
M39B-1	AEGIS® Bearing Protection Ring	
M39C	Baldor-Reliance® Shaft Grounding Brush Assembly	
M39D	Add AEGIS® Colloidal Silver Shaft Coating to Shaft	
<b>Check Total Indicated Runout (TIR)</b>	.....	333
M40A	Check Total Indicated Runout (TIR)	
<b>ABB Ability™</b>	.....	333
M43A	Install ABB Ability™ Smart Sensor for Motors	

## Motor Mod Express®

### Ordering Information

**Note:** Motors made for sale in the U.S. must comply with the Small Motor Rule and the Integral Horsepower Rule (10 CFR 431) including those modified from stock. After any modification, the motor must comply with the minimum efficiency levels if the motor is sold for use in the United States.

Motors sold for use in Canada must comply with the applicable regulations such as Natural Resources Canada if used in that country. Motors sold through distribution into Mexico must be registered and comply with NOM ANCE standards. Motors modified and sold for use in Europe must comply with CE for efficiency and other markings. Other countries have their own specific requirements and certifications for those specific countries.

Order size limited to qty.(1-10) and will ship as a single lot upon completion of modification. To order, specify the catalog number of the stock product and the MOD number. Apply the motor discount to the motor list price. Apply the modification discount symbol MX to the modification list price. Customer will absorb all freight costs when motor is shipped to Fort Smith from field warehouses. For order qty.(1-5) lead times will be as indicated and are subject to availability of stock motors in the Fort Smith Warehouse. Orders with qty.(6-10) may require additional scheduling lead time, contact your ABB sales office.

**Lead times indicated are subject to availability of stock motors in the Fort Smith Warehouse.**

Customer will absorb all freight costs when motor is shipped to Fort Smith from field warehouses.

**Note:** Some modifications do not apply to explosion-proof motors. Contact your local sales office for approval.

Modifications for the 449T frame 2300 Volt and above as well as the 5008-5810 frame motors have been specifically created for the General Purpose Motor (GPM) product family of Large AC TEFC motors. Factory modifications are not available for the 450 and 500 IEC frame sizes in the GPM product. Some of the modifications may be used on the Severe Duty or Ammonia Compressor ODP products, however please check with the factory prior to order entry to ensure availability of required modification.

#### MOD Express Cancellation Policy

Should it be necessary to cancel an order for a motor after it is modified, but before it ships – a cancellation charge of double the modification charge will be invoiced to the customer. Any MOD order cancelled before modification is completed is subject to 25% cancellation charge.

Once shipped, modified motors returned at purchaser's expense will be invoiced at double the MOD fee plus 10% restock fee.

**Note:** Mod Express for RPM AC, RPM III DC and V\*S Master is available. Contact your local Sales Office for details.

Some modifications cannot be performed on UL, CSA, or UL/CSA Certified Grinders, Buffers, or Belt Sanders without voiding the Certification.

In such instances, the Certification Mark(s) would need to be removed.

Please contact your sales representative.

#### Note

**NEW** modifications are indicated with **RED** titles.

All lead times indicated are subject to availability of stock motors and parts in the Fort Smith warehouse. Please check stock availability before quoting lead time.

Some conversions may not be allowed if they result in a change of operating parameters that affect efficiency or change the EISA or NRCan classification of compliant motors.

Modification prices do not include the cost of the motor, speed reducer, etc.

## Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

### Balance

#### M1A

#### Dynamic Balance of Rotor

Re-balance stock motor to special balance NEMA 42 through 5810 frame.

Squirrel Cage Type			
NEMA Frame	Standard Balance	Special Balance	List Price Per Motor
40 - 140	0.15"/s	0.08"/s	256
180 - 210	0.15"/s	0.08"/s	621
250 - 280	0.15"/s	0.08"/s	894
320 - 360	0.15"/s	0.08"/s	1734
400	0.15"/s	0.10"/s	2100
440	0.15"/s	0.10"/s	2192
5008 - 5810	0.15"/s	0.10"/s	2342

**Note:** Balance units are for velocity in inches per second.  
Special balance is the standard level for IEEE-841 (2009).

TWO  
DAYS

### Bearings

#### M2A

#### Sealed

This modification provides the option of replacing standard bearings in AC motors with sealed bearings.

NEMA Frame	List Price Per Motor (2 Bearings)
48, 56	181
143 - 145	185
182 - 184	233
213 - 215	233
254 - 256	435
284 - 286	435
324 - 326	562
364 - 365	562

**Note:** Grease fittings will be replaced with slotted head pipe plugs.  
Contact your sales representative.

**Grease fittings will be replaced with slotted head pipe plugs unless otherwise specified.**

TWO  
DAYS

## Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

### Bearings continued...

#### M2B

#### Ball to Roller 1800 RPM or Below

THREE  
DAYS

Roller bearings have the capability to handle higher radial loads than ball bearings, but must have high minimum radial loads to operate correctly.

Roller bearings must only be used in heavy belted loads, they are not suitable for coupled loads. Only the stock 449T frames 2300V and above, as well as the TEFC 5000 and 5800 frame GPM TEFC motors with "L" shafts have high strength steel shafts.

Also see the main catalog section for stocked Baldor-Reliance® motors with roller bearings already installed. These stock motors are identified with a "LR" suffix after the catalog number – Example: EM58606LR-2340.

**Does Not Apply to Explosion-Proof Motors or designs that must be built as custom motors.**

NEMA Frame	List Price Per Motor
449T*	1948
5008L - 5810L	1948

**Note:** \*449T - Applicable to 449T, 2300 volt and above.

Users must ensure to not exceed load carrying capability of installed roller bearing.

Maximum load capability of a rating can be provided.

If unsure of your load data, a belt load datasheet can be provided to assist.

#### M2F

#### Add Isolated Bearings NEMA 56 Through 5810 (SKF Insocoat or equivalent)

TWO  
DAYS

If insulating both bearings, the addition of M39A is recommended.

NEMA Frame	List Price (x2 per set)
56 - 145T	539
182T - 184T	560
213T - 215T	762
254T - 256T	1168
284T - 286T	1466
324T - 326T	1634
364T - 365T	1693
404T - 405T	1772
444T - 445T	1852
447T - 449T	3174
5008 - 5810	1305 (1 Bearing)

**Note:** Totally Enclosed (TEFC) 449T frames at 2300/4000V and 5008-5810 motors come standard with an insulated opposite drive bearing.

For pricing on 2300/4000V 449T frame, please use 5008-5810 frame adder

# Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

## Brake Motors

### M3D

#### Change Stearns Brake Voltage

Brake coils will be changed to allow operation from different voltage supplies for both 50 and 60 hertz AC or from DC supplies.

External brake coil lead connections will be brought from the brake or from the motor conduit box when necessary in the application.

Specify brake lead location, voltage of brake coil, frequency of supply source. (Allow 2 weeks for brake coil delivery.)

**List price: \$282 per brake (plus any difference in coil cost).**

CONTACT  
YOUR  
LOCAL  
SALES  
OFFICE

## Conduit Box

### M4A

#### Tap or Provide Additional Lead Hole

Lead outlet hole in conduit box with dimensions as shown below will be tapped to accept threaded conduit as shown in "Optional threaded hole..." column below.

An additional clearance hole or threaded hole may be supplied if specified. Use same list adder for threaded hole.

NEMA Frame	Hole Diameter *	Stock Motor	Optional Threaded Hole	List Price Per Motor
		For Conduit Size	For Conduit Size	
48 - 145T	7/8"	1/2"	3/4"	126
182 - 215T	1-1/16"	3/4"	1"	126
254 - 256T	1-3/8"	1"	1-1/4"	206
284 - 326T	2"	1-1/2"	2"	206
364 - 365T	2-1/2"	2"	2-1/2"	276
404 - 405T	3"	2 1/2"	3"	300
444 - 447T	3"	2-1/2"	3"	300

**Note:** \* Stock motor lead holes are not threaded except on Dirty Duty and Chemical Process motors.

Extra lead holes do not apply to Explosion-Proof motors.

If additional hole is needed, specify hole diameter and exact location.

Contact your sales representative for application assistance.

TWO  
DAYS

## Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

### Conduit Box continued...

<b>M4B</b>	<b>Rotate Conduit Box Lead Opening</b> Specify lead opening location facing conduit box <b>List Price Per Motor: \$147</b>	TWO DAYS
------------	--	----------

<b>M4F</b>	<b>Replace Die Cast Aluminum Conduit Box</b> Install cast iron conduit box with drilled and tapped entrance hole.	TWO DAYS
------------	--	----------

NEMA Frame	List Price Per Motor
42 - 56	162
143 - 215T	187
254 - 286T	230
324 - 365T	368

<b>M4G</b>	<b>Add Conduit Box for Thermostat or Heater Leads</b> <b>Not for Explosion-Proof motors</b>	CONTACT YOUR LOCAL SALES OFFICE
------------	--	---------------------------------

NEMA Frame	List Price Per Motor
56 - 145T	441
182 - 215T	515
254 - 365T	778
404 - 449T	984



# Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

## Cord

### M5A

#### Install Line Cord in Conduit Box or Terminal Panel

TWO DAYS

Heavy duty, industrial type SO oil resistant cord with ground will be installed in conduit box or terminal panel. Strain relief included.

Plug not included.

**Does Not Apply to Explosion-Proof Motors.**

Some modifications cannot be performed on UL, CSA, or UL/CSA Certified Grinders, Buffers, or Belt Sanders without voiding the Certification.

In such instances, the Certification Mark(s) would need to be removed.

Please contact your sales representative.

Wire Gauge	Stock Motor		Six Feet or Less List Price	Each Additional Foot to Ten Max List Price
	Single Phase	Three Phase		
18	10	7	133	10
16	13	10	133	11
14	18	15	154	14
12	25	20	162	15

**Note:** Specify voltage and rotation facing drive end of motor.

### M5B

#### Install 6 Foot, 3 Conductor, Type SO Cord With Plug

TWO DAYS

With ground plug for 115VAC, single phase only.

**Does Not Apply to Explosion-Proof Motors.**

Some modifications cannot be performed on UL, CSA, or UL/CSA Certified Grinders, Buffers, or Belt Sanders without voiding the Certification.

In such instances, the Certification Mark(s) would need to be removed.

Please contact your sales representative.

Hp	List Price Per Motor
1 Hp and smaller	142

**Note:** Advise rotation facing drive end of motor

## Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

### Drains

#### M7A

#### Add Condensation Drain Holes

TWO  
DAYS

A maximum of two additional drilled holes will be made in both endplates of 215T frame and smaller TEFC motors.

A maximum of one additional plastic T-drain fitting will be installed in both endplates of 254T frame and larger TEFC motors.

##### Does Not Apply to Explosion-Proof Motors

NEMA Frame	List Price Per Motor
215 and Smaller	223
254 - 449	303

**Note:** Indicate position of drain holes in each endplate.

#### M7C

#### Close Standard Condensation Drain Holes

TWO  
DAYS

Close existing drain holes with plugs.

##### Does Not Apply to Explosion-Proof Motors

NEMA Frame	List Price Per Motor
215 and Smaller	185
254 - 449	223

#### M7D

#### Add Breather Drains to Cast Iron Explosion-Proof Motor

TWO  
DAYS

Drain Type	List Price Per Motor
UL Listed Explosion-Proof Drain - ANSI 316 S.S.	389
UL Listed Explosion-Proof Drain - Crouse-Hinds ECD	437

## Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

### Dripcovers

#### M8A

#### Install Dripcover on TEFC or ODP

TWO  
DAYS

NEMA Frame	List Price Per Motor ODP or TEFC
48 - 145	147
182 - 184	158
213 - 215	176
254 - 256	202
284 - 286	244
324 - 326	270
364 - 365	488
404-405 (NEMA Frame)	488
444 - 449 (NEMA Frame)	692

### Leads

#### M10B

#### Reconnect Motor from Nine Leads to Three

TWO  
DAYS

##### Specify Voltage When Ordering

NEMA Frame	List Price Per Motor
42 - 145	162
182 - 184	251
213 - 215	333
254 - 256	375
284 - 286	494
324 - 326	624

**Note:** On explosion proof, leads are connected in conduit box.

#### M10D

#### Longer Leads, Additional Leads added

TWO  
DAYS

##### Does Not Apply to Explosion-Proof Motors.

Some modifications cannot be performed on UL, CSA, or UL/CSA Certified Grinders, Buffers, or Belt Sanders without voiding the Certification.

In such instances, the Certification Mark(s) would need to be removed.

Please contact your sales representative.

NEMA Frame	Number of Leads	List Price		
		18 Inches	24 Inches	36 Inches
42-286	3 - 12 Leads	215	218	224
	3 Leads	324	335	346
	6 Leads	358	380	403
324-449	9 Leads	392	425	459
	12 Leads	425	470	515

**Note:** If lead requirements are longer than 8 feet contact your sales representative.

## Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

### Lubrication

#### M11A

### Install Low Temperature Lubricant in Bearings

TWO  
DAYS

#### (Single Shield or Open Bearing)

Standard grease is Exxon POLYREX® EM, with bearing operating temperature range of -15° to +250°F.

For low temperature operation, please specify either Aeroshell #7 or Mobil Temp SHC-32 low temperature grease which allows an operating temperature range for bearings of -55° to +200°F.

New bearings are installed when grease is changed.

#### Does Not Apply to Explosion-Proof Motors

NEMA Frame	List Price Per Motor
48	126
56 - 145T	135
182 - 184T	145
213 - 215T	150
254 - 256T	192
284 - 286T	213
324 - 326T	299
364 - 365T	319
404 - 405T	507
444 - 449T	700

**Note:** Low temperature operation below -25C (-13F)

#### M11B

### Add High Temperature Grease

TWO  
DAYS

Standard grease is Exxon POLYREX® EM, with bearing operating temperature range of -15° to +250°F. For High temperature operation, please specify Mobilith SHC 220 high temperature grease which allows an operating temperature range for bearings of -40° to +302°F.

New bearings are installed when grease is changed.

#### Does Not Apply to Explosion-Proof Motors

NEMA Frame	List Price Per Motor
48	126
56 - 145T	135
182 - 184T	145
213 - 215T	150
254 - 256T	192
284 - 286T	213
324 - 326T	299
364 - 365T	319
404 - 405T	507
444 - 449T	700

**Note:** Contact your sales representative to discuss application prior to ordering.

## Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

### Seals

#### M12A

#### Install Oil Seals

Nitrile is the standard oil seal material

**Does Not Apply to Explosion-Proof Motors**

NEMA Frame	List Price Each
48, 56	342
143T - 145T	342
182T - 184T	378
213T - 215T	417
254T - 256T	574
284T - 286T	673
324T - 326T	760
364T - 365T	956
404T - 405T	956
444T - 449T*	1008

\* For 449T frames 2300 Volt and above, consult M27B Mod.

CONTACT  
YOUR  
LOCAL  
SALES  
OFFICE

#### M12B

#### Install Inpro/Seal® Drive End Only

Inpro/Seal® VBX is the standard material used.

**Note:** Contact your sales representative for opposite drive end installation or order IEEE 841 motor from stock.

**Does Not Apply to Explosion-Proof Motors**

NEMA Frame	List Price Each
143T-215T	1070
254-256T	1340
284-286T	1428
324-326T	1516
364-365T	1739
404-405T	1825
444-449T	2224
5008 - 5810	1101

FOUR  
DAYS

#### M12C

#### Install V-Ring Seals to Motor

Add set of V-Ring seals to the motor. One seal in the DE, and another seal between the fan and ODE Endplate.

TENV and OPEN motors only get a seal on the DE.

**List per motor: \$266**

TWO  
DAYS

## Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

### Mountings

#### M13A

#### Add Rigid Base

Weld stamped steel base to steel band explosion proof motor unless motor meets VEM or VEL.

Not available if conversion results in motors that fall under EISA/NRCAN requirements.

NEMA Frame	List Price Per Motor
42 - 48	168
56	172
143 - 145T	172
182 - 184T	209
213 - 215T	251

**Note:** Not available for cast iron motors.

TWO  
DAYS

#### M13B

#### Install NEMA C-Face Steel Band Motor Construction

Add to rigid base mounted motor.

**Not for explosion proof motors.**

NEMA Frame	List Price Per Motor
42, 48 & 56	221
143 - 145T (1)	221
182 - 184T (1)	242
213 - 215T (1)	293
254 - 256T (2)	557
284 - 286T (2)	756
324 - 326T (2)	988

**Note:** (1) These motors will have a non-NEMA BA dimension when C-Face is added.

(2) Applies to ODP only.

**Open motors having type numbers beginning with "34" cannot be modified to C-Face. Contact your local sales office for details.**

TWO  
DAYS  
  
284T &  
LARGER  
SUBJECT TO  
CASTING  
AVAILABILITY

#### M13C-1

#### Install NEMA C-Face - Cast Iron Construction

Install Cast Iron Endplate where aluminum die cast parts are supplied as standard.

**Does Not Apply to Explosion-Proof Motors, See M13G**

NEMA Frame	List Price Per Motor
48 & 56	234
143 - 145T (1)	234
182 - 184T (1)	282
213 - 215T (1)	324
254 - 256T	717
284 - 286T	988
324 - 326T	1069
364 - 365T	1153
404 - 405T	1438
444 - 449T	1725

**Note:** (1) These motors will have a non-NEMA BA dimension when C-Face is added.

Specify C-face or Standard horizontal endplate.

TWO  
DAYS

## Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

### Mountings continued...

#### M13C-2

#### Install NEMA C-Face – IEEE 841 Motors

TWO  
DAYS

NEMA Frame	NEMA C-Face Price
284 - 365TC	1022
324 - 326TC	1590
364 - 326TC	1611
404 - 405TC	1793
447 - 449TC	1902

#### M13D

#### Add D-Flange

CONTACT  
YOUR  
LOCAL  
SALES  
OFFICE

Some motors may be converted to D-Flange mounting and meet NEMA BA dimensions.

All other frame sizes needing D-Flange mounting please order as custom motor.

**Does Not Apply to Explosion-Proof Motors**

##### Steel Band

NEMA Frame	List Price Per Motor
140	221
180	598
320	986

##### Cast Iron

NEMA Frame	List Price Per Motor
180	321 * †
250	1069 * †
280	1192 *
320	1357 *

**Note:** \* TEFC motors only

† Must start with motor that already has C-Face on it.

#### M13E

#### Remove Rigid Base from Foot Mounted Steel Band Motors

TWO  
DAYS

NEMA Frame	List Price Per Motor	NEMA Frame	List Price Per Motor
42 - 48	224	213 - 215T	372
56	230	254 - 256T	529
143 - 145T	230	284 - 286T	600
182 - 184T	279	324 - 326T	736

**Note:** Bases cannot be removed from explosion proof motors.

# Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

## Mountings continued...

### M13F-1

## Convert Mounting Configuration for Steel Band Motor

TEN DAYS

Available on all Steel Band AC motors through 449T Frame.

For conversion to F2 designs, check available inventory before using Mod. Consists of repositioning endplate vents, condensation drains, and where applicable, the conduit to positions shown in the Mountings chart at the end of Mountings mods.

Converting a steel band motor requires a new steel band frame.

**Does Not Apply to Stainless Steel Band Motors**

**Does Not Apply to Explosion-Proof Motors**

NEMA Frame Enclosure	Specify Mounting configuration using Drawing at the end of ModEx Mountings section		List Price Per Motor
	ODP	TEFC	
UP TO 184T	Yes	Yes	564
213 - 215T	Yes	Yes	564
254 - 326T	Yes	254-6	733
364 - 449T	Yes	Yes	959

### M13F-2

## Convert Mounting Configuration for Cast Iron Motor

THREE DAYS

Available on all Cast Iron AC motors through 449T Frame. For conversion to F2 designs, check available inventory before using Mod.

Consists of repositioning endplate vents, condensation drains, and where applicable, the conduit to positions shown in the Mountings chart at the end of Mountings mods.

**Does Not Apply to Explosion-Proof Motors**

NEMA Frame Enclosure	Specify Mounting configuration using Drawing at the end of ModEx Mountings section		List Price Per Motor
	ODP	TEFC	
UP TO 184T	Yes	Yes	213
213 - 215T	Yes	Yes	213
254 - 326T	Yes	Yes	213
365 - 449T	Yes	Yes	213
5008-5810	No	Yes	414

**Note:** For 5008-5810 Open motors (WPI, WPII), please contact factory to determine if F2 is achievable.



## Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

### Mountings continued...

#### M13G

#### Add C-Face to Explosion-Proof Motors

THREE DAYS

Only available on NEMA frames shown below.

NEMA Frame	List Price Per Motor
56	268
143 - 145T (Steel Band only)	268
284 - 286T	1932
324 - 326T	2643
364 - 365T	2957
404 - 405T	3489

**Note:** Any other frame size must be built as a custom motor.

#### M13I

#### Mount Grinder or Buffer onto Pedestal

TWO DAYS

Price does not include the grinder or buffer, pedestal or any accessories.

Wheel Size	List Price Per Grinder or Buffer
All	213


# Motor Mod Express®

Modification  
Number


Motor Mod Express®  
Description and List Price

Working Days  
Required


## Floor Mountings



Assembly F-1




Assembly F-2




Assembly F-3


## Wall Mountings




Assembly W-1




Assembly W-2




Assembly W-3




Assembly W-4




Assembly W-5



Assembly W-6




Assembly W-7




Assembly W-8

## Ceiling Mountings



Assembly C-1



Assembly C-2

**Note:** For all NEMA mounting configurations, refer to NEMA MG 1-2016.

For more information visit [baldor.com](http://baldor.com) or [new.abb.com/motors-generators](http://new.abb.com/motors-generators)

## Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

### Export Packaging

#### M14A

#### Open Crate Packaging

EIGHT  
DAYS

Replace standard motor packaging with Open Crate.

For NEMA 360 thru 449 frames the open crate has Euro base as standard.

Requests for Euro pallet on NEMA 320 frame and smaller must be made in shipping instructions.

NEMA Frame	Open Crate List Price
56-215	420
254-326	547
364-445	772
447-449	873
5008-5012	1634
5810	1743

#### M14B

#### Totally Enclosed Crate Packaging

EIGHT  
DAYS

Replace standard motor packaging with Enclosed Crate.

For NEMA 360 thru 449 frames the enclosed crate has Euro base as standard.

Requests for Euro pallet on NEMA 320 frame and smaller must be made in shipping instructions.

NEMA Frame	Open Crate List Price
56-215	526
254-326	740
364-445	921
447-449	1070
5008-5012	7323
5810	7979

#### M14C

#### Motor and Nameplate Photograph

FIVE  
DAYS

Take photo of motor and nameplate for FAA Security Endorsement Documents.

Photos will be attached to sales order.

List price per motor: \$85

## Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

### Nameplate

<b>M15A</b>	<p><b>Provide Original Nameplate for Remote Mounting</b></p> <p>Extra nameplate is packed with motor, not mounted. All CSA and UL<sub>R</sub> markings are removed on duplicate nameplates. Shipped loose.</p> <p><b>List per motor: \$123</b>                      <b>5000 Frame and Above: \$369 List</b></p>	TWO DAYS
<b>M15B</b>	<p><b>Replace Nameplate</b></p> <p>Replace motor nameplate which may include customer part numbers, voltage, hertz, etc.</p> <p><b>List per motor: \$147</b>                      <b>5000 Frame and Above: \$400 List</b></p>	TWO DAYS
<b>M15C</b>	<p><b>Laser Engrave Nameplate into Stainless Steel Motor</b></p> <p>Motor nameplate is laser etched on stainless steel band surface up to 210 frame motor</p> <p><b>List per motor: \$147</b></p>	TWO DAYS
<b>M15E</b>	<p><b>Mail Nameplates to Customer</b></p> <p>(All CSA and UL<sub>R</sub> markings are removed on nameplates ordered as a mail out order)</p> <p><b>No Explosion-Proof Nameplates (No Exceptions!)</b></p> <p><b>Order minimum charge of \$31 net. Add \$3.00 net for each additional nameplate.</b></p> <p><b>5000 Frame and above: \$369</b></p> <p><b>Note:</b> No charge orders only accepted if with RA or warranty claim. Nameplates for Explosion-proof motors will not be mailed out, no exceptions.</p>	TWO DAYS
<b>M15F</b>	<p><b>Mark Nameplate with CE</b></p> <p>The motor has to meet IE2 efficiency standards and be ATEX / IECEx approved in order to be CE marked. Does not apply to Div. 1 or Div. 2 classified motors.</p> <p><b>List per motor: \$147</b></p>	TWO DAYS

### Blowers

<b>M16A</b>	<p><b>Add Constant Velocity Blower Unit</b></p> <p>Contact your sales representative for details</p>	TWO DAYS				
<b>M16B</b>	<p><b>Convert from a 3 Phase to a Single Phase Blower</b></p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">NEMA Frame</th> <th style="text-align: left;">List Price Per Motor</th> </tr> </thead> <tbody> <tr> <td>All</td> <td>228</td> </tr> </tbody> </table>	NEMA Frame	List Price Per Motor	All	228	TWO DAYS
NEMA Frame	List Price Per Motor					
All	228					

## Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

### Paint

#### M17A

#### Paint Motor Baldor-Reliance® Stock Paint Color

Baldor-Reliance® Stock colors are: Metallic Gray, Reliance Blue/Green, Gold Super-E, Black, White, Silver, Lite Tan. Stock colors for 5008 and up are:

White, Black, Yellow, Gray and Signal Red. Please specify color on order.

**All orders that call for Epoxy paint require an additional day to allow for complete drying of paint.**

NEMA Frame	Open Crate List Price
42 - 215T	147
254 - 449T	579
5008 - 5812	1359

TWO  
DAYS

#### M17B

#### Paint Motor or Parts Customer Specified Color

Painted parts include, but are not limited to, fan covers, conduit boxes, drip covers, etc.

Please provide color chip or RAL number on order.

**All orders that call for Epoxy paint require an additional day to allow for complete drying of paint.**

**List price: Contact your local sales office for quote.**

TWO  
DAYS

### Lifting Lugs

#### M18A

#### Add Lifting Lugs Up to a 326T Frame Size

NEMA Frame	List Price Per Motor
48 - 145T	219
182 - 215T	272
254 - 286T	353
324 - 326T	431

TWO  
DAYS

## Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

### Hardware

#### M20A

#### Exchange Plated Hardware with Stainless Steel

TWO  
DAYS

Replaces all mounting hardware for fan cover, conduit box, bearing retainers, thru-bolts, and frame bolts with 304 stainless steel hardware.

NEMA Frame	List Price Per Motor
56-184	337
213-215	373
254-256	431
284-286	488
324-326	561
364-405	647
444-445	792
447-449	876
5008-5810	3410

**Note:** 5008 frame and up, pricing includes grease and relief tubes.

### Space Heaters

#### M21A

#### Add Space Heaters to TEFC or Open Motors

TWO  
DAYS

Standard space heater voltage is 110VAC. Heaters for 230 or 460 volts are available. Specify circuit voltage.

#### Does Not Apply to Explosion-Proof Motors

NEMA Frame	List Price Per Motor
145T and Smaller	319
182 - 215T	402
254 - 365T	598
404 - 449T	680

**Note:** Strip type space heaters are standard.

# Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

## Thermal Protectors

### M23A

### Thermostats

TWO DAYS

#### One or More Thermostats Laced to Winding

For over temperature protection.

These are pilot circuit devices only with leads into conduit box tagged "JJ".

Specify normally open or closed contacts.

All ECP motors require hermetically sealed thermostats to maintain Division 2 marking.

#### Does Not Apply to Explosion-Proof Motors

NEMA Frame	Number of Devices	Standard List Price Per Motor	Hermetically Sealed for Division 2
Single Phase	1	185	N/A
Three Phase 42 - 215T	3 (3)	209	304
Three Phase 254 - 449T	3 (3)	557	653
Direct Current 48 - 215T	1	209	N/A

**Note:** (3) In Series with two leads into conduit box. Normally open are in parallel.

## Winding Thermocouples

(3 per motor, 6 foot standard length)

### M24A

### Iron Constantan (3 per motor)

TWO DAYS

Specify location.

#### Does Not Apply to Explosion-Proof Motors

NEMA Frame	List Price Per Thermocouple
42 - 215T	202
254 - 449T	417

**Note:** Thermocouples are installed on end turns.

## Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

### Winding Thermistors

#### M25A

#### Thermistors

Thermistors are normally applied in sets of three (3) per motor, One (1) per phase.

**Does Not Apply to Explosion-Proof Motors**

List Price per motor: \$669

TWO  
DAYS

### Tropicalization

#### M26A

#### Protection of Windings and Mechanical Parts

Protection from tropical environments.

NEMA Frame	List Price Per Motor
Through 215T	244
254 - 365T	350
404 - 449T	598
5008 - 5810	1609

**Note:** For 5008-5810 this includes epoxy coating of rotor and stator and additional fungus protection

TWO  
DAYS

### Weatherproofing

#### M27A

#### Treatment of Windings and Mechanical Parts

Protection from the elements or high moisture areas.

**Does Not Apply to Explosion-Proof Motors**

NEMA Frame	List Price Per Motor
42 - 215T	238
254 - 365T	1112
404 - 449T	1306

**Note:** "Dirty Duty", "CP" and "ECP" motors are weatherproofed as standard.

TWO  
DAYS



# Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

## Shaft Modifications

Includes modifications to existing shafts only. Not applicable if new shaft is required. Price each modification per table. One or both bearings will be replaced after shaft modification is complete.

FIVE DAYS

NEMA Frame	List Price Per Modification	NEMA Frame	List Price Per Modification
42 - 145T	219	254T - 256T	291
182 - 184T	230	284 - 286T	291
ASM62 (5)	270	324-326T	337
213 - 215T	319	364-365T	359
ASM75 (5)	319	404-405T	401

**Note:** (5) Arbor Saw Motors.

### M29A

#### Drill and Tap One Hole in End of Shaft or Mill Flat on Shaft Extension.

THREE DAYS

Provide details on order.  
Price this modification per table above.

### M29B

#### Convert from TEFC to TEAO

THREE DAYS

Cut off shaft extension for external fan.  
Price this modification per table above.  
**Does Not Apply to Explosion-Proof Motors**

### M29C

#### Threading

FIVE DAYS

Specify right hand or left hand thread, also type and length of thread.  
Price this modification per table above.

## Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

### Shaft Modifications continued...

#### M29D

#### Convert “T” Frame to “U” Frame Shaft Dimension or Smaller (TS)

FIVE  
DAYS

Shorten shaft and reduce overall diameter. Provide details on order.

For “U” frame conversion on 280, 320, 360, and 440 frames, please enter custom order. Not available through Mod Express.

NEMA Shaft	Conversion of T Frame to TS or U Frame	List Price Per Motor
143 thru 145T		219
182 thru 215T		402
254 thru 286T		916
324 thru 365T		1364
404 thru 449T		2248

#### M29F

#### Shorten Shafts Without Reducing the Overall Diameter

THREE  
DAYS

Shortening the shaft may cause the motor to fall out of NEMA standards. If motor falls out of NEMA standards, the nameplate will be designated with a “TZ” to signify short shaft.

NEMA Shaft	List Price Per Motor
48 - 145T	232
182 - 215T	247
254 - 256T	253
324 - 326T	267
364 - 365	281
404 - 405	281
447 - 449	294

## Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

### Tach and Encoder Mounting Kits

#### M31D

#### Add Encoder Kit to Inverter Duty V\*S Master or RPMAC Motor

TWO  
DAYS

Order encoders separately.

Encoders can be found in the Variable Speed AC motors section.

NEMA Frame	RPMAC Frame	List Price Per Motor
56 - 215T	FL/RL180-210	191
254T - 404T	FL/RL 250-400	397
444T - 449T	FL/RL440	619
5008 - 5810	N/A	2614

**Note:** For 5008-5810 frames motors come with HS35R Dynapar encoders.

#### M31E

#### Additional Mounted Encoder Options for IDRPM Motors

TWO  
DAYS

List price includes encoder and mounting to motor.

Type	Frame Size	Mfg.	PPR	Mag or Optical	Conn Type	Input Voltage VDC	List Price
HS35	All	BEI	1024	O	MS-TL	5-28	1834
HS35	All	BEI	2048	O	MS-TL	5-28	1834
LP35	All	BEI	1024	M	Term. Block	5-15	1834
LP35	All	BEI	1024	M	MS-TL	5-15	1834
LP35	All	BEI	1024	M	MS-ST	5-15	1834
HS20	All	Dynapar	1024	O	MS-TL	5-26	1834
ST85	All	Northstar	1024	O	EPIC Latch	5-15	3226
HS35M	All	Avtron	1024	M	MS-ST	5-24	1995
HS35M	All	Avtron	1024	M	EPIC Latch	5-24	1995

## Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

### Testing

Contact your local sales office for original factory test reports.

#### M32A

### CSA C390 Method 1 Equivalent to IEEE 112 Method B Performance Testing

SEVEN \*  
DAYS

Three phase stock motors will be tested under lab conditions according to CSA C390 (equivalent to IEEE 112b).

Complete test data will be supplied.

Bearings are replaced after testing.

NEMA Frame	List Price Per Motor
42 - 215	2400
254 - 320	3901
360 - 449	4694
5008 - 5810	5250

**Note:** For 449T frames 2300V and above use 5000 frame price – motors will be tested at factory.

#### M33A

### Short Motor Test

SEVEN \*  
DAYS

Three phase or single phase motors will have any or all of the following motor characteristics measured. Test data will be supplied. All data will be taken on cold motor.

- No Load Current
- Full Load Current
- Breakdown Torque
- Locked Rotor (Starting) Current
- Locked Rotor Torque
- Hi-Potential Test

NEMA Frame	List Price Per Motor
42 - 215T	400
254 - 449T	731

**Note:** Not available for 449T Frame 2300 Volt and up.

#### M33B

### Routine Motor Test

SEVEN \*  
DAYS

This is a test reported per IEEE Std. 112 – 2004 Annex B.

All data will be taken on a cold motor.

Test includes:

- No Load Current
- Locked Rotor Current
- High-Potential
- Winding Resistance

NEMA Frame	List Price Per Motor
42 - 215T	270
254 - 449T*	496

**Note:** \* Lead time is dependent on Test Lab availability. Contact your local sales office.

For more information visit [baldor.com](http://baldor.com) or [new.abb.com/motors-generators](http://new.abb.com/motors-generators)

## Motor Mod Express®

Modification  
Number

Motor Mod Express®  
Description and List Price

Working Days  
Required

### Testing continued...

#### M33C

#### Complete Performance Test

SEVEN \*  
DAYS

A Complete test uses a dynamometer to verify nameplate description and electrical design characteristics. The motor is allowed to achieve its full load temperature rise before making performance measurements. Testing conducted per IEEE Std 112-2004 Annex C. Test report includes:

- No Load Current
- Full Load Current
- Locked Rotor Current
- High-Potential
- Winding Resistance
- Full Load Heat Run
- Temperature Rise
- Full Load Slip
- Measure breakdown and starting torques
- Measure efficiency at 100%, 75%, 50% of full load
- Measure power factor at 100%, 75% 50% of full load

NEMA Frame	List Price Per Motor
42 - 215T	2400
254 - 320T	3597
360T - 449T*	8787

**Note:** For 449T frame 2300 Volt and up please see M32A.

#### M33D

#### Calibration Test

\* CONTACT  
YOUR  
LOCAL  
SALES  
OFFICE

This test consists of 0 to 125% rated load test measurement of speed, torque, current, power factor and efficiency at rated voltage.

The data is provided as a curve plotted on Baldor-Reliance® standard format.

Tests may also be performed as a witnessed test.

NEMA Frame	Calibration Test
42 - 215T	2160
254T - 320T	2878
360T - 449T*	7913

**Note:** Not available for 449T frame 2300 Volt and above.

#### M33E

#### Sound Measurement Test

SEVEN \*  
DAYS

Two tests are available to measure the sound produced by the motor at idle and operated from a line power supply.

The basic test is an overall sound measurement (one band). The Noise test that verifies sound levels per procedures defined in IEEE-85 under a No Load Condition showing an octave band analysis is also available.

Double these prices for witnessed tests.

**Note:** Sound tests must be performed in Fort Smith or the Motor R&D Lab in Greenville. Allow for extra shipping time and freight charges from plant.

NEMA Frame	Calibration Test
42 - 215T	985
254 - 445T	1472
447 - 449T	3595

**Note:** \* Lead time is dependent on Test Lab availability. Contact your local sales office.

For more information visit [baldor.com](http://baldor.com) or [new.abb.com/motors-generators](http://new.abb.com/motors-generators)

## Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

### Terminal Blocks

#### M35A

#### Install IEC Terminal Blocks in Conduit Box and Connect Leads

TWO  
DAYS

IEC Frame, stocked with terminal blocks.

Advise how motors leads are to be connected.

**Does Not Apply to Explosion-Proof Motors**

NEMA Frame	List Price
34 FRAME - 56-143T	228
35 FRAME - 56-145T	245
182-184	272
213-215	298
254-256	342
284-286	353
324-326	1031
364-365	1031
404-405	1031
444-449	1031

# Motor Mod Express®

Modification  
Number

Motor Mod Express®  
Description and List Price

Working Days  
Required

## Starters

### Add Magnetic or Manual Starter to Grinder or Buffer

Mounted and wired on Baldor-Reliance® industrial grinders and buffers.  
Starters are in NEMA 1 enclosure and have the push button in cover.  
Available only as factory installed options.  
Lead time is dependent on delivery of the starter.  
**Price of the starter is included.**

#### M36A

#### Starter – Single Phase

TWO  
DAYS

Full voltage control.  
Some modifications cannot be performed on UL, CSA, or UL/CSA Certified Grinders, Buffers, or Belt Sanders without voiding the Certification.  
In such instances, the Certification Mark(s) would need to be removed.  
Please contact your sales representative.

Grinder Wheel Size	Buffer Hp	Manual	Magnetic
		115/230 Volts List Price	115 Volts 230 Volts List Price
6"	1/3	503	825 922
7"	N/A	503	825 922
8"	3/4	503	946 922
10"	1	503	946 922
N/A	1-1/2	503	946 810
12"	2	Standard Equipment	803* 810*

**Note:** Specify voltage when ordering.  
\*Price includes allowance for omission of standard starter.

#### M36B

#### Starter – Three Phase

TWO  
DAYS

Full voltage control. **Price of the starter is included.**  
Some modifications cannot be performed on UL, CSA, or UL/CSA Certified Grinders, Buffers, or Belt Sanders without voiding the Certification.  
In such instances, the Certification Mark(s) would need to be removed.  
Please contact your sales representative.

Grinder Wheel Size	Buffer Hp	Manual	Magnetic
		208-230/460 Volts List Price	208-230 Volts 460 Volts List Price
7"	N/A	581	922 850
8"	N/A	581	922 850
10"	3/4	581	922 850
12"	1	Standard Equipment	650* 597*
12"	2	Standard Equipment	650* 597*

**Note:** Specify voltage when ordering.  
\*Price includes allowance for omission of standard starter.

## Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

### Starters continued...

#### M36C

#### Magnetic Starter – Three Phase

With Low Voltage Control.

Price of the starter is included.

TWO  
DAYS

Grinder Wheel Size	Buffer Hp	Magnetic With 110 Volt Control Circuit Transformer	
		208-230 Volts List Price	460 Volts List Price
7"	N/A	2071	2291
8"	N/A	2071	2291
10"	3/4	2071	2291
12"	1	2032*	2074*
12"	2	2032*	2074*
14"	5	2032*	2074*
14"	7-1/2	2032*	2074*

**Note:** Specify voltage when ordering.

\*Price includes allowance for omission of standard starter.

#### M36D

#### Overload Protection for Dust Control Unit

Price of the starter is included.

TWO  
DAYS

NEMA Frame	List Price
All	619

**Note:** Must be used with magnetic control. Contact your sales representative for details.



# Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

## Shaft Grounding

A shaft ground may be specified by many HVAC, pump and conveyor manufacturers to mitigate the effects of Adjustable Speed Drive circulating currents and prolong bearing life. Shaft grounding is available as an option on Baldor-Reliance custom motors or can be installed on a stock motor in Motor Mod Express®. On applications where washdown or debris may be present, mounting the ground internally on the motor (as custom) may be required.

**NOTE:** A shaft ground is a sparking device not suited for explosion-proof Division 1 or 2 applications, even when mounted internally.

ABB offers three main types of shaft grounding devices:

- **M39A - Shaft Grounding Systems**
- **M39B - Shaft Grounding Rings**
- **M39C - Shaft Grounding Brush**

### M39A

#### Shaft Grounding Systems

The SGS™ (Shaft Grounding Systems) design is a robust, enclosed unit designed for harsh environments.

Mounts to the opposite drive end of the motor on TEFC, TENV, TEBC and ODP motors.

**Does Not Apply to Explosion-Proof or Division 2 Motors**



THREE DAYS

NEMA Frame	List Price
56 - 449T	1231

### M39B-1

#### AEGIS® Bearing Protection Ring

NEMA Frame	Shaft Diameter	External List Price	Internal List Price
56	0.625	221	663
140T, 180	0.875	232	696
180T, 210	1.125	244	732
210T, 250U	1.375	258	774
250T, 280U	1.625	322	966
280T, 320U, 320TS, 360TS	1.875	343 (1)	1,029
320T, 360U, 400TS	2.125	379 (1)	1,137
360T, 400U, 440TS	2.375	456 (1)	1,368
400T, 440U	2.875	643 (1)	1,929
440T	3.375	766 (1)	2,298

(1) Motors over 100 Hp / 75 kW require an additional modification to add an insulated bearing on the opposite drive end. Reference Mod M2F to add for one insulated bearing on the ODE of the motor.

**Note:** For this modification, the AEGIS Bearing Protection Ring mounts to the drive end of the motor.

TWO DAYS

## Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

### Shaft Grounding continued...

#### M39C

#### Baldor-Reliance® Shaft Grounding Brush Assembly

TWO  
DAYS

Add external or internal shaft grounding brush to motor endplate.

Brush contacts motor shaft diameter.

**Does Not Apply to Explosion-Proof Motors**

NEMA Frame	External List Price	Internal List Price
48, 56	221	663
140	232	696
180	244	732
210	258	774
250	272	816
280	291 (1)	873 (1)
320	318 (1)	954 (1)
360	350 (1)	1050 (1)
400	386 (1)	1158 (1)
440	431 (1)	1293 (1)
5008 - 5810	1306 (1)	



(1) Motors over 100 Hp / 75 kW require an additional modification to add an insulated bearing on the opposite drive end. Reference Mod M2F to add for one insulated bearing on the ODE of the motor.

#### M39D

#### Add AEGIS® Colloidal Silver Shaft Coating to Shaft

TWO  
DAYS

Add a coating of AEGIS colloidal silver to shaft of motor to enhance the conductivity of the surface.

**List price: \$350**

## Motor Mod Express®

Modification Number	Motor Mod Express® Description and List Price	Working Days Required
---------------------	---	-----------------------

### Check Total Indicated Runout (TIR)

#### M40A

#### Check Total Indicated Runout (TIR)

Check C-face and shaft run out.  
If applicable check foot flatness.

**List price: \$123**

TWO  
DAYS

### ABB Ability™

#### M43A

#### Install ABB Ability™ Smart Sensor for Motors

Pricing includes the installation of a Smart Sensor to NEMA 140 - 440 Cast Iron frames.

All sensors mounted through the mod shop come with a 2 year web subscription.

Specify between F1, F2 or F3 mounting orientation.

**List per motor: \$774**

**Note:** Choosing F3 position may require lifting provisions to be omitted.

CONTACT  
YOUR  
LOCAL  
SALES  
OFFICE